

HPD UNIQUE IDENTIFIER: 21202

CLASSIFICATION: workstation screen, partition, wall panel, ceiling

PRODUCT DESCRIPTION: An acoustic panel with a solid colour (SC) profile, ideal for applications with exposed edges such as workstations and partitions, available in three sound absorbing thicknesses, 9mm, 12mm and 24mm

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
 Basic Method

Threshold Disclosed Per

- Material
 Product

Threshold level

- 100 ppm
 1,000 ppm
 Per GHS SDS
 Other

Residuals/Impurities

Residuals/Impurities
Considered in 0 of 1 Materials

Explanation(s) provided
for Residuals/Impurities?

- Yes No

All Substances Above the Threshold Indicated Are:

Characterized Yes Ex/SC Yes No
% weight and role provided for all substances.

Screened Yes Ex/SC Yes No
All substances screened using Priority Hazard Lists with results disclosed.

Identified Yes Ex/SC Yes No
All substances disclosed by Name (Specific or Generic) and Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | **SUBSTANCE** | *RESIDUAL OR IMPURITY*

GREENSCREEN SCORE | HAZARD TYPE

POLYESTER [**POLYESTER** **NoGS**]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen
Benchmark or List translator Score ... UNK

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

9mm: alpha w 0.78 / NRC 0.85 (200mm airgap) 12mm: alpha w 0.8 / NRC 0.85 (200mm airgap) 24mm: Ecoustic® SC 24mm is ideal for medium to high frequency absorption and achieves an alpha w 0.45 / NRC 0.65 (Direct Fix), alpha w 0.82 / NRC 0.9 (150mm airgap), alpha w 0.95 / NRC 0.95 (200mm airgap)

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: Voc Ecoustic Emission Test

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1 and Option 2

Third Party Verified?

- Yes
 No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2020-03-06

PUBLISHED DATE: 2020-07-30

EXPIRY DATE: 2023-03-06



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

POLYESTER

#: 100.0000 - 100.0000

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Other: Polyester

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities not considered because they were not disclosed by manufacture.

OTHER MATERIAL NOTES: No Residual content disclosed by manufactureAll substances in this material are below the reportable threshold.

POLYESTER

ID: 113669-95-7

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2020-03-06

#: 100.0000 - 100.0000

GS: NoGS

RC: None

NANO: No

SUBSTANCE ROLE: Insulator

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: No recycled content present in 0.98" or 1.97" thicknesses

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

Voc Ecoustic Emission Test

CERTIFYING PARTY: **Third Party**

ISSUE DATE: **2019-**

EXPIRY DATE:

CERTIFIER OR LAB: **Berkeley**

APPLICABLE FACILITIES: **Berkeley Analytical**

12-18

Analytical

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES:

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Designed for the Environment: Easy to disassemble and separate into the appropriate recycling systems, Ecoustic® SC can be recycled - Low VOC + Oeko Tex Certification: The low VOC and Oeko Tex certified Ecoustic® SC is non-toxic, non-irritant and non-allergenic

MANUFACTURER INFORMATION

MANUFACTURER: **Unika Vaev**ADDRESS: **19 Ohio Ave****Norwich Connecticut 06360, United States**WEBSITE: **<https://unikavaev.com/products/acoustic-category/ceiling/>**CONTACT NAME: **Unika Vaev**TITLE: **Purchasing Assistant**PHONE: **800-237-1625**EMAIL: **cathyl@unikavaev.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types**AQU** Aquatic toxicity**CAN** Cancer**DEV** Developmental toxicity**END** Endocrine activity**EYE** Eye irritation/corrosivity**GEN** Gene mutation**GLO** Global warming**LAN** Land toxicity**MAM** Mammalian/systemic/organ toxicity**MUL** Multiple**NEU** Neurotoxicity**NF** Not found on Priority Hazard Lists**OZO** Ozone depletion**PBT** Persistent, bioaccumulative, and toxic**PHY** Physical hazard (flammable or reactive)**REP** Reproductive**RES** Respiratory sensitization**SKI** Skin sensitization/irritation/corrosivity**UNK** Unknown**GreenScreen (GS)****BM-4** Benchmark 4 (prefer-safer chemical)**BM-3** Benchmark 3 (use but still opportunity for improvement)**BM-2** Benchmark 2 (use but search for safer substitutes)**BM-1** Benchmark 1 (avoid - chemical of high concern)**BM-U** Benchmark Unspecified (due to insufficient data)**LT-P1** List Translator Possible 1 (Possible Benchmark-1)**LT-1** List Translator 1 (Likely Benchmark-1)**LT-UNK** List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)**NoGS** No GreenScreen.**Recycled Types****PreC** Pre-consumer recycled content**PostC** Post-consumer recycled content**UNK** Inclusion of recycled content is unknown**None** Does not include recycled content**Other Terms:****GHS SDS** Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet**Inventory Methods:****Nested Method / Material Threshold** Substances listed within each material per threshold indicated per material**Nested Method / Product Threshold** Substances listed within each material per threshold indicated per product**Basic Method / Product Threshold** Substances listed individually per threshold indicated per product**Nano** Composed of nano scale particles or nanotechnology**Third Party Verified** Verification by independent certifier approved by HPDC**Preparer** Third party preparer, if not self-prepared by manufacturer**Applicable facilities** Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this

