

HPD UNIQUE IDENTIFIER: 27278

CLASSIFICATION: 07 72 33 Roof Hatches

PRODUCT DESCRIPTION: Roof Hatches provide safe and convenient access to commercial building roof areas using interior ladders and stairs. Nystrom's complete line of Roof Hatch and Safety products meet building codes, fire and life safety requirements. Tested for wind-uplift, forced entry and air infiltration where basic wind speed reached greater than 70 miles per hour. Nystrom's Personnel Roof Hatches provide safe access to roof areas on your building. The Hurricane Hatch is tested to a higher performance standard. Sized for ladder, ship stair, and service stair access with optional safety railings, grab bars and a variety of materials and finishes. This HPD covers Nystrom's Personnel Roof Hatch (RHUA) with Aluminum Curb and Cover, with multiple insulation options. Roof Hatches also available in Steel.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Table with 4 columns: Inventory Reporting Format, Threshold Level, Residuals/Impurities, and Explanation(s) provided for Residuals/Impurities? Each column contains radio button options and descriptive text.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY GREENSCREEN SCORE | HAZARD TYPE PERSONNEL AND HURRICANE ROOF HATCH (ALUMINUM CURB AND COVER) [ALUMINUM BM-1 | END | RES | PHY STEEL NoGS POLYISOCYANURATE FOAM LT-P1 ETHYLENE/PROPYLENE/DIENE TERPOLYMER (EPDM) LT-UNK SC:CELLULOSE Not Screened ETHENE, POLYMER WITH 1-PROPENE LT-UNK ZINC LT-P1 | END | MUL | PHY | AQU CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE LT-UNK CARBON BLACK BM-1 | CAN PENTANE LT-P1 | MUL | PHY | MAM | AQU STAINLESS STEEL NoGS POLYSTYRENE LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 0 Contents highest concern GreenScreen Benchmark or List translator Score ... BM-1 Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Special conditions applied: BiologicalMaterial

[LEED v4] "Yes ex/SC" result is due only to materials and substances for which Special Conditions were applied. Thus "Yes ex/SC" does not disqualify the product for the LEED v4 Materials and Resources Disclosure and Optimization credit, Option 1.

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.2, and discloses hazards associated with all substances present at or above 1000 parts per million (ppm) in the finished product, along with the role and percent weight.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method – Not tested

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1

Third Party Verified?

- Yes No

PREPARER: Self-Prepared

VERIFIER: VERIFICATION #:

SCREENING DATE: 2022-01-25

PUBLISHED DATE: 2022-01-25

EXPIRY DATE: 2025-01-25

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpdc-collaborative.org/hpd-2-2-standard

PERSONNEL AND HURRICANE ROOF HATCH (ALUMINUM CURB AND COVER)

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities were considered by following the suggestions of Emerging Best Practices. More than 95% of this product consists of metal alloys, for which Pharos CML may consider the various alloying elements as "Known or Potential Residuals". Therefore, these components have been included in the Substance Notes instead of as individual content entries. Components are listed by name, CASRN, percent by weight (as per supplier SDS), and relevant GreenScreen score.

OTHER PRODUCT NOTES: Percent by weight of substances given as ranges to account for material differences between product lines.

ALUMINUM

ID: 7429-90-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2022-01-25 9:44:44

#: 90.0000 - 92.0000 GS: BM-1 RC: Both NANO: No SUBSTANCE ROLE: Alloy element

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
RES	AOEC - Asthmagens	Asthmagen (Rs) - sensitizer-induced
PHY	EU - GHS (H-Statements) Annex 6 Table 3-1	H228 - Flammable solid [Flammable solids - Category 1 or 2]
PHY	EU - GHS (H-Statements) Annex 6 Table 3-1	H261 - In contact with water releases flammable gases [Substances and mixtures which, in contact with water, emit flammable gases - Category 2 or 3]

SUBSTANCE NOTES: GreenScreen Benchmark® assessment score of BM-1 was provided by the HPD Builder Tool. Recycled content confirmed by supplier for majority of Aluminum used in product: range from 5% to about 60%, with the typical content averaging about 35%. Documentation from supplier provides the following composition for alloying elements that may individually exceed the declared threshold: <6.6% Magnesium [7439-95-4; LT-UNK]; <1.5% Silicon [7440-21-3; LT-UNK]; <1.8% Iron [7439-89-6; LT-P1]; <1.1% Chromium [7440-47-3; LT-P1]; <4.0% Zinc [7440-66-6; LT-P1]; <1.9% Manganese [7439-96-5; LT-P1].

STEEL

ID: 12597-69-2

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2022-01-25 9:44:45

#: 6.3000 - 6.5000 GS: NoGS RC: UNK NANO: No SUBSTANCE ROLE: Alloy element

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Hold-open arm, bracket, springs, fasteners.

POLYISOCYANURATE FOAM

ID: 9063-78-9

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2022-01-25 9:44:45

#: 0.5000 - 1.2000

GS: LT-P1

RC: None

NANO: No

SUBSTANCE ROLE: Insulator

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Foam insulation.

ETHYLENE/PROPYLENE/DIENE TERPOLYMER (EPDM)

ID: 25038-36-2

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-01-25 9:44:46**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Continuous gasket seal.

SC:CELLULOSE

ID: SC:Bio

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **Not Screened**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
Hazard Screening not performed		

SUBSTANCE NOTES:
 Version: SCBioMats/2018-02-23
 Category: Tree-based materials
 Identifier: 65996-61-4

This disclosure does not provide information on allergens, hyper-accumulation of metals, production of any toxic substances during normal metabolic activities, pesticides, and other potential hazards or sources of hazards which may be found in certain biological materials. Facer for polyisocyanurate insulation. Identified on the US EPA Safer Chemical Ingredient List (Green Circle - Verified Low Concern).

ETHENE, POLYMER WITH 1-PROPENE

ID: 9010-79-1

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-01-25 9:44:46**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Red grip handle.

ZINC

ID: 7440-66-6

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-01-25 9:44:47**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
PHY	EU - GHS (H-Statements) Annex 6 Table 3-1	H260 - In contact with water releases flammable gases which may ignite spontaneously [Substances and mixtures which, in contact with water, emit flammable gases - Category 1]
AQU	EU - GHS (H-Statements) Annex 6 Table 3-1	H400 - Very toxic to aquatic life [Hazardous to the aquatic environment (acute) - Category 1]
AQU	EU - GHS (H-Statements) Annex 6 Table 3-1	H410 - Very toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 1]
PHY	EU - GHS (H-Statements) Annex 6 Table 3-1	H250 - Catches fire spontaneously if exposed to air [Pyrophoric liquids; Pyrophoric solids - Category 1]

SUBSTANCE NOTES: Galvannealed latch, fasteners.

CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE

ID: 65997-17-3

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-01-25 9:44:47**

#: **0.0100 - 0.1000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Structure component**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Facer for polyisocyanurate insulation.

CARBON BLACK

ID: 1333-86-4

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-01-25 9:44:48**

#: **0.0100 - 0.1000** GS: **BM-1** RC: **None** NANO: **No** SUBSTANCE ROLE: **Pigment**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CAN	IARC	Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources

SUBSTANCE NOTES: Continuous gasket seal, foam insulation. Form-specific hazards: airborne particles of respirable size – occupational setting. GreenScreen Benchmark® assessment score of BM-1 was provided by the HPD Builder Tool. Specific guidelines have been created to address known issues related to transparency and disclosure for several materials (“Special Conditions”), including those with Form-Specific Hazards such as Carbon Black; however, this function is not yet available in the HPD Builder.

PENTANE

ID: 109-66-0

#: **Impurity/Residual** GS: **LT-P1** RC: **None** NANO: **No** SUBSTANCE ROLE: **Impurity/Residual**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
PHY	EU - GHS (H-Statements) Annex 6 Table 3-1	H225 - Highly flammable liquid and vapour [Flammable liquids - Category 2]
MAM	EU - GHS (H-Statements) Annex 6 Table 3-1	H304 - May be fatal if swallowed and enters airways [Aspiration hazard - Category 1]
AQU	EU - GHS (H-Statements) Annex 6 Table 3-1	H411 - Toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 2]

SUBSTANCE NOTES: Blowing agent used in polyisocyanurate insulation.

STAINLESS STEEL

ID: **12597-68-1**

#: **0.0100 - 0.1000** GS: **NoGS** RC: **UNK** NANO: **No** SUBSTANCE ROLE: **Alloy element**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Fasteners

POLYSTYRENE

ID: **9003-53-6**

#: **0.0000 - 1.5000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Insulator**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Alternate insulation: 1" polystyrene used in conjunction with 1" polyisocyanurate.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

CDPH Standard Method – Not tested

CERTIFYING PARTY: Self-declared

ISSUE DATE: 2019-08-

EXPIRY DATE:

CERTIFIER OR LAB: N/A

APPLICABLE FACILITIES: N/A

12

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES:

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

SAFETY RAILING

HPD URL: <https://www.nystrom.com/products/fall-protection/safety-railings>

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

OSHA compliant fall protection safety railings and posts specifically designed for Roof Hatches, Smoke Vents and Floor Doors.

Section 5: General Notes

MANUFACTURER INFORMATION

MANUFACTURER: Nystrom
ADDRESS: 9300 73rd Avenue North
 Minneapolis MN 55428, United States
WEBSITE: www.Nystrom.com

CONTACT NAME: Sandy McWilliams
TITLE: Director of Business Development
PHONE: (800) 547-2635
EMAIL: SMcWilliams@nystrom.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)
BM-2 Benchmark 2 (use but search for safer substitutes)	NoGS No GreenScreen.
BM-1 Benchmark 1 (avoid - chemical of high concern)	
BM-U Benchmark Unspecified (due to insufficient data)	
LT-P1 List Translator Possible 1 (Possible Benchmark-1)	

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.