EZ-Path® Cable Tray Retrofit Device by Specified Technologies Inc.

Health Product Declaration v2.2

created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 29141
CLASSIFICATION: 07 84 13.16 Penetration Firestopping Devices
PRODUCT DESCRIPTION: The EZ Path® Cable Tray Retrofit Device is designed to restore the ratings for overfilled cable tray penetrations. The device features a built-in fire and smoke sealing system that installs around existing cable trays and fastens to the barrier surface. The EZ Path® Cable Tray Retrofit Device consists of a heavy gauge galvanized steel housing containing intumescent materials that expand rapidly when exposed to fire or high temperatures to close off the void area. Its unique two-piece design installs around existing cable tray penetrations in fire-rated walls restoring the fire-rating of penetrations even when loaded to 100% cable fill. Applications: EZ Path® Cable Tray Retrofit Device restores non-compliant overfilled cable tray conditions in fire-rated walls. Cable capacity ranges from 25 to 100% visual fill. The two-piece split device facilitates installation around existing cable trays. The steel housing fastens directly to the wall surface or combines with steel adapter plates or SpecSeal Composite Sheet when addressing oversized openings. EZ Path® Cable Tray Retrofit Device is available in a range of widths to accommodate for cable trays as narrow as 12 in. to as wide as 18 in. No additional putty or sealant is required for installation. Performance: EZ Path® Cable Tray Retrofit Device is UL Certified in accordance with ASTM E814 (UL1479) and CAN/ULC-S115. Systems are available for wall construction with ratings up to and including 2 Hr. Refer to UL System for more details.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format
- ○ Nested Materials Method
- ◉ Basic Method

Threshold Disclosed Per
- ○ Material
- ◉ Product

Threshold Level
- ○ 100 ppm
- ◉ 1,000 ppm
- ○ Per GHS SDS
- ○ Other

Residuals/Impurities
- ◉ Considered
- ○ Partially Considered
- ○ Not Considered

Explanation(s) provided for Residuals/Impurities?
- ◉ Yes ○ No

All Substances Above the Threshold Indicated Are:

Characterized ○ Yes Ex/SC ◉ Yes ○ No

% weight and role provided for all substances.

Screened ○ Yes Ex/SC ◉ Yes ○ No

All substances screened using Priority Hazard Lists with results disclosed.

Identified ○ Yes Ex/SC ○ Yes ◉ No

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | *RESIDUAL OR IMPURITY*
GREENSCREEN SCORE | HAZARD TYPE

EZ-PATH® CABLE TRAY RETROFIT DEVICE [GRAPHITE LT-UNK UNDISCLOSED LT-UNK UNDISCLOSED BM-2 POLYPROPYLENE GLYCOL LT-P1 | RES METHYLENE BISPHENYL DIISOCYANATE (PURE MDI) LT-UNK | MUL | RES | CAN | SKI | EYE POLYMERIC MDI (PMDI) LT-UNK | MUL | RES | CAN UNDISCLOSED LT-UNK CARBON BLACK BM-1 | CAN UNDISCLOSED LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... BM-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

None.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE *See Section 3 for additional listings.*

VOC emissions: N/A

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1

Third Party Verified?
- ○ Yes
- ◉ No

PREPARER: Self-Prepared
VERIFIER:
VERIFICATION #:

SCREENING DATE: 2022-07-06
PUBLISHED DATE: 2022-07-08
EXPIRY DATE: 2025-07-06

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- *Basic Inventory method with Product-level threshold.*
- *Nested Material Inventory method with Product-level threshold*
- *Nested Material Inventory method with individual Material-level thresholds*

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

EZ-PATH® CABLE TRAY RETROFIT DEVICE

PRODUCT THRESHOLD: 1000 ppm RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: There are no residuals in this product

OTHER PRODUCT NOTES: There are no residuals in this product.

GRAPHITE ID: 7782-42-5

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-07-06 10:35:59**

%: **2.0000 - 4.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Intumescent**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the intumescent material in the device.

UNDISCLOSED ID: Undisclosed

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-07-06 10:35:59**

%: **2.0000 - 4.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the intumescent material in the device.

UNDISCLOSED ID: Undisclosed

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-07-06 10:36:00**

%: **1.0000 - 3.0000** GS: **BM-2** RC: **None** NANO: **No** SUBSTANCE ROLE: **Plasticizer**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the intumescent material in the device.

POLYPROPYLENE GLYCOL ID: 25322-69-4

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-07-06 10:36:00**

%: **0.5000 - 1.0000** GS: **LT-P1** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
RES	AOEC - Asthmagens	Asthmagen (Rs) - sensitizer-induced

SUBSTANCE NOTES: This is part of the intumescent material in the device.

METHYLENE BISPHENYL DIISOCYANATE (PURE MDI)

ID: **101-68-8**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-07-06 10:36:01**

%: **0.5000 - 1.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
MUL	US EPA - PPT Chemical Action Plans	EPA Chemical of Concern - Action Plan published
RES	AOEC - Asthmagens	Asthmagen (G) - generally accepted
CAN	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels
RES	AOEC - Asthmagens	Asthmagen (Rs) - sensitizer-induced
RES	MAK	Sensitizing Substance Sah - Danger of airway & skin sensitization
RES	US EPA - PPT Chemical Action Plans	Inhalation sensitizer causing asthma and lung damage
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1	H317 - May cause an allergic skin reaction [Skin sensitization - Category 1]
EYE	EU - GHS (H-Statements) Annex 6 Table 3-1	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]
RES	EU - GHS (H-Statements) Annex 6 Table 3-1	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled [Respiratory sensitization - Category 1]
CAN	EU - GHS (H-Statements) Annex 6 Table 3-1	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]

SUBSTANCE NOTES: This is part of the intumescent material in the device.

POLYMERIC MDI (PMDI)

ID: **9016-87-9**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-07-06 10:36:01**

%: **0.1000 - 0.5000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
MUL	US EPA - PPT Chemical Action Plans	EPA Chemical of Concern - Action Plan published
RES	AOEC - Asthmagens	Asthmagen (G) - generally accepted
CAN	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels
RES	AOEC - Asthmagens	Asthmagen (Rs) - sensitizer-induced
RES	MAK	Sensitizing Substance Sah - Danger of airway & skin sensitization
RES	US EPA - PPT Chemical Action Plans	Inhalation sensitizer causing asthma and lung damage

SUBSTANCE NOTES: This is part of the intumescent material in the device.

UNDISCLOSED ID: **Undisclosed**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-07-06 10:36:02**

%: **0.1000 - 0.2000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Surfactant**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the intumescent material in the device.

CARBON BLACK ID: **1333-86-4**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-07-06 10:36:02**

%: **0.0500 - 0.1000** GS: **BM-1** RC: **None** NANO: **No** SUBSTANCE ROLE: **Pigment**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CAN	IARC	Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources

SUBSTANCE NOTES: This is part of the intumescent material in the device.

UNDISCLOSED ID: **Undisclosed**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-07-06 10:36:03**

%: **0.0500 - 0.1000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Catalyst**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the intumescent material in the device.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS **N/A**

CERTIFYING PARTY: Self-declared
APPLICABLE FACILITIES: All.
CERTIFICATE URL:
https://files.stifirestop.com/5.%20Safety%20Data%20Sheets/1.%20English/SDS_EZ-Path%20Retrofit%20Device.pdf

ISSUE DATE: 2017-05-05
EXPIRY DATE:
CERTIFIER OR LAB: Self-declared.

CERTIFICATION AND COMPLIANCE NOTES: Not appilcable. Not a wet applied product or type of insulation. See SDS under Certificate URL.

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Specifications
All new data comm cable penetrations shall be routed through factorysupplied, maintenance-free, fire-rated pathway devices (Ex. EZ-Path® Fire Rated Pathways). For existing sleeves where cable fill percentage exceeds listed system specifications, a factory-supplied, fire-rated retrofit device shall be installed. The device shall be a two-piece split design with intumescent materials and allow 50 to 100 percent visual fill. The device shall be UL Certified and tested to ASTM E814 (UL1479) and CAN/ULC-S115. The device shall be EZ-Path® Retrofit Device.
Performance
EZ-Path® Retrofit Device is UL Certified in accordance with ASTM E814 (UL 1479 and CAN/ULC-S115). Systems are available for common floor and wall construction with ratings up to and including 2 Hr. L Ratings range from <1 to 10.7 CFM dependent upon cable types, sizes, and configurations. Refer to UL System for more details.
Features & Benefits
• Easy to install.
• No Additional firestopping required.
• Sized for 2” (2.197” to 2.375” or 56 mm to 60 mm OD) and 4” (4.500” or 114 mm) trade size EMT or rigid steel conduit sleeves or stubs
• 50%-100% cable fill
• Works with extended or flush sleeves
• Bring overfilled sleeves back into code compliance!

Section 6: References

MANUFACTURER INFORMATION

MANUFACTURER: **Specified Technologies Inc.**
ADDRESS: **210 Evans Way**
Somerville NJ 08876, United States
WEBSITE: **www.stifirestop.com**

CONTACT NAME: **George Gornick, LEED Green Associate**
TITLE: **Applications Engineer**
PHONE: **800-992-1180, Ext. 1013**
EMAIL: **ggornick@stifirestop.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity
CAN Cancer
DEV Developmental toxicity
END Endocrine activity
EYE Eye irritation/corrosivity
GEN Gene mutation
GLO Global warming
LAN Land toxicity
MAM Mammalian/systemic/organ toxicity
MUL Multiple
NEU Neurotoxicity
NF Not found on Priority Hazard Lists
OZO Ozone depletion
PBT Persistent, bioaccumulative, and toxic
PHY Physical hazard (flammable or reactive)
REP Reproductive
RES Respiratory sensitization
SKI Skin sensitization/irritation/corrosivity
UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)
BM-3 Benchmark 3 (use but still opportunity for improvement)
BM-2 Benchmark 2 (use but search for safer substitutes)
BM-1 Benchmark 1 (avoid - chemical of high concern)
BM-U Benchmark Unspecified (due to insufficient data)
LT-P1 List Translator Possible 1 (Possible Benchmark-1)
LT-1 List Translator 1 (Likely Benchmark-1)
LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)
NoGS No GreenScreen.

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.