SpecSeal® Ready® Split Sleeve Firestop Sleeve by Specified Technologies Inc.

Health Product Declaration v2.2

created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 28186
CLASSIFICATION: 07 84 13.16 Penetration Firestopping Devices
PRODUCT DESCRIPTION: Ready® Split Sleeves are a complete UL® Certified out-of-the-box solution for new or existing cable penetrations through walls. Each sleeve kit contains a precut split metallic sleeve, split mounting escutcheons, split intumescent escutcheon gaskets, wall warning labels, and the amount of putty required to seal both ends. Ready® Split Sleeves are simple in design and installation. Each trade size includes a unique rolled lip design to eliminate potential sharp edges and do away with the need for conduit bushings. Ready® split sleeves are sized to the same O.D. as standard EMT (Electrical Metal Tubing) and will accept EMT accessories such as grounding bushings. Additionally, Ready® Split Sleeves provide an easy method for compliance with the sleeve attachment requirements of the 2015 IBC Section 714.2 and 2018 IBC Section 714.3 without the need for struts or other bracing. Applications Ready® Split Sleeves are used to protect or support cables in both non-rated and rated construction. Ready® split sleeves are suitable for use in all common constructions including concrete floors, concrete walls, concrete block walls, and gypsum board/stud wall assemblies up to 10” (250 mm) thick.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format
- ○ Nested Materials Method
- ◉ Basic Method

Threshold Disclosed Per
- ○ Material
- ◉ Product

Threshold Level
- ○ 100 ppm
- ◉ 1,000 ppm
- ○ Per GHS SDS
- ○ Other

Residuals/Impurities
- ◉ Considered
- ○ Partially Considered
- ○ Not Considered

Explanation(s) provided for Residuals/Impurities?
- ◉ Yes ○ No

All Substances Above the Threshold Indicated Are:

Characterized ○ Yes Ex/SC ◉ Yes ○ No

% weight and role provided for all substances.

Screened ○ Yes Ex/SC ◉ Yes ○ No

All substances screened using Priority Hazard Lists with results disclosed.

Identified ○ Yes Ex/SC ○ Yes ◉ No

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | *RESIDUAL OR IMPURITY*
GREENSCREEN SCORE | HAZARD TYPE

SPECSEAL® READY® SPLIT SLEEVE FIRESTOP SLEEVE [STEEL NoGS GRAPHITE LT-UNK ALUMINA TRIHYDRATE BM-2 | RES UNDISCLOSED LT-UNK CELLULOSE PULP NoGS UNDISCLOSED NoGS UNDISCLOSED LT-UNK UNDISCLOSED LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-UNK

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

None.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE *See Section 3 for additional listings.*

VOC emissions: N/A

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1

Third Party Verified?
- ○ Yes
- ◉ No

PREPARER: Self-Prepared
VERIFIER:
VERIFICATION #:

SCREENING DATE: 2022-04-13
PUBLISHED DATE: 2022-04-13
EXPIRY DATE: 2025-04-13

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- *Basic Inventory method with Product-level threshold.*
- *Nested Material Inventory method with Product-level threshold*
- *Nested Material Inventory method with individual Material-level thresholds*

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

SPECSEAL® READY® SPLIT SLEEVE FIRESTOP SLEEVE

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: There are no residuals in this product.

OTHER PRODUCT NOTES: There are no residuals in this product.

STEEL

ID: 12597-69-2

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-04-13 7:48:07**

%: **75.0000 - 85.0000** GS: **NoGS** RC: **None** NANO: **No** SUBSTANCE ROLE: **Structure component**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is the zinc-plated steel sleeve and escutcheon plate assembly.

GRAPHITE

ID: 7782-42-5

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-04-13 7:48:08**

%: **2.0000 - 7.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Intumescent**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is the intumescent contained in the sleeve gasket and firestop putty dosage.

ALUMINA TRIHYDRATE

ID: 21645-51-2

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-04-13 7:48:08**

%: **2.0000 - 7.0000** GS: **BM-2** RC: **None** NANO: **No** SUBSTANCE ROLE: **Flame retardant**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
RES	AOEC - Asthmagens	Asthmagen (Rs) - sensitizer-induced

SUBSTANCE NOTES: This is a flame retardant contained in the firestop putty dosage.

UNDISCLOSED

ID: Undisclosed

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-04-13 7:48:09**

%: **2.0000 - 7.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the binder system for the firestop putty dosage.

CELLULOSE PULP

ID: **65996-61-4**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-04-13 7:48:09**

%: **1.0000 - 4.0000** GS: **NoGS** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the binder system for the intumescent gaskets.

UNDISCLOSED

ID: **Undisclosed**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-04-13 7:48:10**

%: **0.5000 - 1.5000** GS: **NoGS** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the binder system for the intumescent gaskets.

UNDISCLOSED

ID: **Undisclosed**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-04-13 7:48:10**

%: **0.5000 - 3.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the binder system for the firestop putty dosage.

UNDISCLOSED

ID: **Undisclosed**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2022-04-13 7:48:11**

%: **0.1000 - 1.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This is part of the binder system for the intumescent gaskets.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS **N/A**

CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: All. CERTIFICATE URL: https://files.stifirestop.com/5.%20Safety%20Data%20Sheets/1.%20English/SDS_Ready%20Split%20Sleeve.pdf	ISSUE DATE:	EXPIRY DATE:	CERTIFIER OR LAB:
	2017-07-12		Self-declared.

CERTIFICATION AND COMPLIANCE NOTES: Not appilcable. Not a wet applied product or type of insulation. See SDS under Certificate URL.

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Specifications
All data, video, communication, power, and control cabling shall be installed through sleeves wherever said cables penetrate fire resistance rated barriers. In the case of existing cable installation, a split sleeve device with corresponding split escutcheon plates to facilitate installation around existing cables shall be used. Sleeves shall be sized to accommodate present cable bundle diameter as well as anticipated growth. Split sleeve kit provided with intumescent gaskets and non-hardening intumescent firestop putty. When irregularly shaped openings are encountered, the split sleeve device shall be UL Tested and Certified for this purpose. The split sleeve device shall be UL Certified and tested to the requirements of ASTM E 814 (ANSI/UL 1479) and CAN/ULC-S115. Split sleeve kit shall be UL tested in larger or irregularly shaped openings and include provisions for mounting device in such openings.
Specified Divisions
Division 7 07 84 13 Penetration Firestopping
Division 23 23 00 00 HVAC
Division 26 26 00 00 Electrical
Performance
Ready® split sleeves are UL Tested and Certified in accordance with ASTM E814 (UL1479) and CAN/ULC-S115. Systems are available for cable penetrations through common wall constructions up to and including 4 hours and concrete floors up to 3 hours.
Features & Benefits
• Split Design — For use with existing cables.
• Oversize Openings — UL Tested for larger and irregularly shaped openings
• Ready to Install — No cutting required, no waste!
• Locks Into Place — No support struts and clamps required
• No external firestop seal required — Factory supplied intumescent firestop gasket
• Firestop Putty Provided with Kit — Sufficient to seal ends to 1” (25 mm) depth
• UL Classified and Code Compliant
• For Rated and Non-Rated Barriers — Putty seal impedes the passage of fire, smoke, superheated gases, particulate dust, and minimizes noise transmission

Section 6: References

MANUFACTURER INFORMATION

MANUFACTURER: **Specified Technologies Inc.**
ADDRESS: **210 Evans Way**
Somerville NJ 08876, United States
WEBSITE: **www.stifirestop.com**

CONTACT NAME: **George Gornick, LEED Green Associate**
TITLE: **Applications Engineer**
PHONE: **800-992-1180, Ext. 1013**
EMAIL: **ggornick@stifirestop.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity
CAN Cancer
DEV Developmental toxicity
END Endocrine activity
EYE Eye irritation/corrosivity
GEN Gene mutation
GLO Global warming
LAN Land toxicity
MAM Mammalian/systemic/organ toxicity
MUL Multiple
NEU Neurotoxicity
NF Not found on Priority Hazard Lists
OZO Ozone depletion
PBT Persistent, bioaccumulative, and toxic
PHY Physical hazard (flammable or reactive)
REP Reproductive
RES Respiratory sensitization
SKI Skin sensitization/irritation/corrosivity
UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)
BM-3 Benchmark 3 (use but still opportunity for improvement)
BM-2 Benchmark 2 (use but search for safer substitutes)
BM-1 Benchmark 1 (avoid - chemical of high concern)
BM-U Benchmark Unspecified (due to insufficient data)
LT-P1 List Translator Possible 1 (Possible Benchmark-1)
LT-1 List Translator 1 (Likely Benchmark-1)
LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)
NoGS No GreenScreen.

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.