

HPD UNIQUE IDENTIFIER: 1322311680

CLASSIFICATION: 09 67 00 Fluid-Applied Flooring

PRODUCT DESCRIPTION: Dex-O-Tex Quik-Glaze is a state of the art, high solids, Low Odor, and UV stable aliphatic polyaspartic topcoat. Some typical floor applications include: Cold storage areas, food service preparation areas, beverage service areas, decorative entry foyers, high traffic areas, promenade decks, labs, pharmaceutical production, and areas exposed to chemical use. ADVANTAGES • Fast Cure • Low Odor • Clear or Pigmented • High Build • High Elongation • High tear strength • Excellent UV resistance • Excellent abrasion resistance • Chemical resistant • High Gloss finish • CDPH 1350 approval • Antimicrobial additive available FINISH OPTIONS See Standard Epoxy and Urethane Color Chart available at www.dexotex.com Also available in custom colors with different skid resistant profiles

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	For all contents above the threshold, the manufacturer has:
☒ Nested Materials Method	☒ 100 ppm	Completed in 6 of 6 Materials	Characterized ☒ Yes ☐ No
☐ Basic Method	☐ 1,000 ppm	Explanation(s) provided for Residuals/Impurities? ☒ Yes ☐ No	Provided weight and role.
Threshold Disclosed Per	☐ Per GHS SDS		Screened ☒ Yes ☐ No
☐ Material	☐ Other		Provided screening results using HPDC-approved methods.
☒ Product			Identified ☒ Yes ☐ No
			Provided name and CAS RN or other identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

NESTED MATERIAL | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

POLYMER [**ASPARTIC ACID, N,N'-(METHYLENEBIS(2-METHYL-4,1-CYCLOHEXANEDIYL))BIS-, 1,1',4,4'-TETRAETHYL ESTER** **LT-P1**] MUL

] POLYMER 3 [**HEXANE, 1,6-DIISOCYANATO-, HOMOPOLYMER** **LT-P1**] SKI] **SOLVENT** [**METHOXYISOPROPYL ACETATE** **LT-UNK**] MAM

| EYE] **POLYMER 2** [**DESMOPHEN XP 7068** **LT-P1**] MUL] **WATER** [**WATER BM-4**] **MONOMER** [**HEXAMETHYLENE DIISOCYANATE** **LT-UNK**] RES | SKI | EYE | MAM]

Number of Greenscreen BM-4/BM3 contents ... 1

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed following the HPD Standard version 2.3. This HPD was produced using primary information from the manufacturer, including CAS numbers and SDS when needed. The manufacturer has made every effort to report the substances in this product to the listed threshold. This is a voluntary, self-reported effort. Any errors or omissions shall be considered a human error and therefore reported to the manufacturer. The manufacturer shall not be liable for omissions. All materials/substances present in the final product were screened at or above 100 ppm, and all potential hazards associated with the product have been disclosed.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 85 Regulatory (g/l): 50

Does the product contain exempt VOCs: No

Are colorants available that do not increase the VOC content of the base paint when tinted: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario

VOC content: VOC Content

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Option 1.

Pre-checked for LEED v4.1 Option 1.

Third Party Verified?	PREPARER: Self-Prepared	SCREENING DATE: 2025-06-10
☐ Yes	VERIFIER:	PUBLISHED DATE: 2025-06-10
☒ No	VERIFICATION #:	EXPIRY DATE: 2028-06-10

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

POLYMER

%: 26.3800 - 46.1600

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: No impurities are listed above the threshold by Quartz or Pharos databases. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data as declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES: Percentages of >10% are used to disguise formulas covered as intellectual property.

ASPARTIC ACID, N,N'-(METHYLENEBIS(2-METHYL-4,1-CYCLOHEXANEDIYL))BIS-, 1,1',4,4'-TETRAETHYL ESTER

ID: 136210-32-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-06-10 5:16:34

%: 100.0000

GreenScreen: LT-P1

RC: UNK

NANO: No

SUBSTANCE ROLE: Polymer species

HAZARD TYPE

LIST NAME AND SOURCE

WARNINGS

MUL

German FEA - Substances Hazardous to Waters

Class 3 - Severe Hazard to Waters

ADDITIONAL LISTINGS

LIST NAME AND SOURCE

NOTIFICATION

None found

No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Data quality score = 1

POLYMER 3

%: 20.4400 - 34.0300

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: No impurities are listed above the threshold by Quartz or Pharos databases. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data as declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES: Percentages of >10% are used to disguise formulas covered as intellectual property.

HEXANE, 1,6-DIISOCYANATO-, HOMOPOLYMER

ID: 28182-81-2

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-06-10 5:16:35	
%: 100.0000	GreenScreen: LT-P1	RC: UNK	NANO: No	SUBSTANCE ROLE: Polymer species
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
SKI	GHS - New Zealand		Skin sensitisation category 1	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found			No listings found on Additional Hazard Lists	
SUBSTANCE NOTES: Data quality score = 2				

SOLVENT

%: 6.5900 - 19.7800

PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Polymeric Material
RESIDUALS AND IMPURITIES NOTES: No impurities are listed above the threshold by Quartz or Pharos databases. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data as declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.		

OTHER MATERIAL NOTES: Percentages of >10% are used to disguise formulas covered as intellectual property.

METHOXYISOPROPYL ACETATE

ID: 108-65-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-06-10 5:16:35	
%: 100.0000	GreenScreen: LT-UNK	RC: UNK	NANO: No	SUBSTANCE ROLE: Solvent
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
MAM	GHS - Japan		H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]	
EYE	GHS - New Zealand		Eye irritation category 2	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
RESTRICTED LIST	Green Science Policy Institute (GSPI)		GSPI - Six Classes Precautionary List	
			Some Solvents	
SUBSTANCE NOTES: Data quality score = 1				

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: No impurities are listed above the threshold by Quartz or Pharos databases. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data as declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES:

DESMOPHEN XP 7068

ID: 136210-30-5

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-06-10 5:16:35

%: 100.0000

GreenScreen: LT-P1

RC: UNK

NANO: No

SUBSTANCE ROLE: Polymer species

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
MUL	German FEA - Substances Hazardous to Waters	Class 3 - Severe Hazard to Waters

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Data quality score = 1

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: No impurities are listed above the threshold by Quartz or Pharos databases. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data as declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES:

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-06-10 5:16:36	
%: 100.0000	GreenScreen: BM-4	RC: UNK	NANO: No	SUBSTANCE ROLE: Diluent
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
None found			No warnings found on HPD Priority Hazard Lists	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
EXEMPT	European Union / European Commission (EU EC)		EU - REACH Exemptions	
			Exempted from REACH Annex IV listing due to intrinsic safety	
SUBSTANCE NOTES: Data quality score = 2				

MONOMER

%: 0.0300 - 0.0900

PRODUCT THRESHOLD: 100 ppm RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: No impurities are listed above the threshold by Quartz or Pharos databases. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data as declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES:

HEXAMETHYLENE DIISOCYANATE

ID: 822-06-0

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-06-10 5:16:34	
%: 100.0000	GreenScreen: LT-UNK	RC: UNK	NANO: No	SUBSTANCE ROLE: Monomer
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
RES	MAK	Sensitizing Substance Sah - Danger of airway & skin sensitization		
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]		
EYE	EU - GHS (H-Statements) Annex 6 Table 3-1	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]		
MAM	EU - GHS (H-Statements) Annex 6 Table 3-1	H331 - Toxic if inhaled [Acute toxicity (inhalation) - Category 3]		
SKI	GHS - New Zealand	Skin irritation category 2		

EYE	GHS - New Zealand	Eye irritation category 2
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1
MAM	GHS - Japan	H370 - Causes damage to organs [Specific target organs/systemic toxicity following single exposure - Category 1]
EYE	GHS - Japan	H318 - Causes serious eye damage [Serious eye damage / eye irritation - Category 1]
SKI	GHS - Japan	H314 - Causes severe skin burns and eye damage [Skin corrosion / irritation - Category 1]
SKI	GHS - Australia	H314 - Causes severe skin burns and eye damage [Skin corrosion/irritation - Category 1A or 1B or 1C]
SKI	GHS - New Zealand	Skin sensitisation category 1
EYE	GHS - Korea	H319 - Causes serious eye irritation [Serious eye damage/irritation - Category 2]
SKI	GHS - Korea	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
SKI	GHS - Malaysia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
MAM	GHS - Korea	H311 - Toxic in contact with skin [Acute toxicity (dermal) - Category 3]
MAM	Québec CSST - WHMIS 1988	Class D1A - Very toxic material causing immediate and serious toxic effects
MAM	GHS - Japan	H311 - Toxic in contact with skin [Acute Toxicity (dermal) - Category 3]
MAM	GHS - Malaysia	H331 - Toxic if inhaled [Acute toxicity (inhalation) - Category 3]
MAM	GHS - New Zealand	Acute dermal toxicity category 3
MAM	GHS - Korea	H330 - Fatal if inhaled [Acute toxicity (inhalation) - Category 2]
MAM	GHS - Australia	H330 - Fatal if inhaled [Acute toxicity (inhalation) - Category 1 or 2]
EYE	GHS - Malaysia	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]
RES	GHS - Japan	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled [Respiratory sensitization - Category 1A]
MAM	GHS - Korea	H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]
MAM	GHS - New Zealand	Acute inhalation toxicity category 1

MAM	GHS - Japan	H330 - Fatal if inhaled [Acute toxicity (inhalation: vapor) - Category 1]
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Perkins+Will (P+W)	P&W - Precautionary List
		Precautionary list of substances recommended for avoidance
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CP II)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022
		Formulated Consumer Products
SUBSTANCE NOTES: Data quality score = 2		

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2022-03-24 00:00:00	CERTIFIER OR LAB: Berkeley
APPLICABLE FACILITIES: This is not a facility level certification.	EXPIRY DATE:	Analytical
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Certificate No: 220413-03		

VOC CONTENT	VOC Content	
CERTIFYING PARTY: Self-declared	ISSUE DATE: 2022-04-29 00:00:00	CERTIFIER OR LAB: Crossfield
APPLICABLE FACILITIES: This is not facilities-based.	EXPIRY DATE:	
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: 86 /l		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

No accessories were added because this must be installed by professional installers who will use their tools and methods. Exact methods are determined by site-specific conditions therefore additional tools and products are not known.

LIMITATIONS

- If sub-surface cracks move due to continued thermal flexing or mechanical loads or building settlement, Dex-O-Tex Quik-Glaze may reflect those cracks to some degree.
- Dex-O-Tex SC Membrane may be used as a waterproofing and crack isolation membrane prior to system application.
- Moisture vapor emission rates (MVER) in excess of 10 lbs/1000 sq/ft/per 24 hr. period per ASTM F1869, or an RH in excess of 84% per ASTM F2170 requires the application of Vapor Control 1P.
- Vapor control primers, sloping, smoothing or leveling compounds, crack repair or isolation, waterproof membranes or other supplementary items may be required for proper installation at an additional cost. Consult with Crossfield Products Corp. for specific recommendations.

WARRANTY

All sales are subject to the Crossfield Terms and Conditions effective on the date the purchase order is received. The Terms and Conditions are incorporated herein in full by this reference. The Terms and Conditions are set forth at (www.dexotex.com) and will also be sent by mail or fax to the purchaser upon request. By placing an order, the Buyer acknowledges that it has read and agrees to the provisions of the Terms and Conditions.

Crossfield Products Corp. assumes no responsibility or liability for any errors or omissions in the content of this document. The information contained is subject to change without notice.

MANUFACTURER INFORMATION

MANUFACTURER: **Crossfield Products Corp.**
ADDRESS: **3000 E Harcourt Street**
Rancho Dominguez, CA 90221
COUNTRY: **USA**

WEBSITE: **<https://dex-o-tex.com>**
CONTACT NAME: **Dung Huynh**
TITLE: **R&D Director**
PHONE: **310-886-9100**
EMAIL: **dungh@cpcmail.net**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

LAN Land toxicity

MAM Mammalian/systemic/organ toxicity

MUL Multiple

NEU Neurotoxicity

NF Not found on Priority Hazard Lists

OZO Ozone depletion

PBT Persistent, bioaccumulative, and toxic

PHY Physical hazard (flammable or reactive)

REP Reproductive

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (due to insufficient data)

LT-P1 List Translator Possible 1 (Possible Benchmark-1)

LT-1 List Translator 1 (Likely Benchmark-1)

LT-UNK List Translator Benchmark Unknown

NoGS No GreenScreen.

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content

PostC Post-consumer recycled content

UNK Inclusion of recycled content is unknown

None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material

Nested Method / Product Threshold Substances listed within each material per threshold indicated per product

Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and

