HELMICOL 3031 B by Helmitin Inc.

Health Product Declaration v2.2 created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 23886

CLASSIFICATION: 09 65 00 Resilient Flooring

PRODUCT DESCRIPTION: HELMICOL 3031 is a two-component solvent-free, epoxy nose caulking adhesive formulated for use with rubber and vinyl stair treads. Helmicol 3031 is designed to fill the void between the nosing of the stair tread and the nosing of the step. HELMICOL 3031 may also be used to permanently install luxury vinyl tile and plank flooring, resilient sheet vinyl flooring, rubber tile flooring and rubber sheet flooring and rubber and vinyl stair treads.

Section 1: Summary

CONTENT INVENTORY

- Inventory Reporting Format
- C Nested Materials Method
- Basic Method
- Threshold Disclosed Per
- O Material
- O Product

- Threshold level C 100 ppm C 1,000 ppm C Per GHS SDS C Other
- Residuals/Impurities C Considered Partially Considered Not Considered Explanation(s) provided for Residuals/Impurities? C Yes C No

Basic Method / Product Threshold

All Substances Above the The Characterized	reshold Indicated Are: ○ Yes Ex/SC ⊙ Yes ○ No					
% weight and role provided i	for all substances.					
Screened	○ Yes Ex/SC					
All substances screened using Priority Hazard Lists with results disclosed.						
Identified	○ Yes Ex/SC					
All substances disclosed by Name (Specific or Generic) and Identifier.						

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY GREENSCREEN SCORE | HAZARD TYPE

HELMICOL 3031 B [LIMESTONE LT-UNK 4-NONYLPHENOL (BRANCHED) LT-1 | AQU | END | MUL | REP | DEV | SKI | PBT DIAMINOPOLYPROPYLENE GLYCOL LT-P1 | MUL N-(2-AMINOETHYL)PIPERAZINE LT-P1 | SKI | MUL SILICON DIOXIDE BM-1 | CAN 1,4-BIS(AMINOCYCLOHEXYL)METHANE LT-P1 | MUL] Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen

Benchmark or List translator Score ... BM-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Ingredients above 1000 ppm and meeting US GHS SDS disclosure requirements are disclosed.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT Material (g/l): <12</td> Regulatory (g/l): 50

Does the product contain exempt VOCs: No Are ultra-low VOC tints available: N/A **CERTIFICATIONS AND COMPLIANCE** See Section 3 for additional

listings. VOC emissions: VOC Emissions VOC content: VOC Content Management: ISO 9001:2015 Quality management systems

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed.

Third Party Verified?

○ Yes○ No

PREPARER: Self-Prepared VERIFIER: VERIFICATION #: SCREENING DATE: 2021-02-18 PUBLISHED DATE: 2021-02-23 EXPIRY DATE: 2024-02-18 This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

	HELMICOL 3031 B						
	PRODUCT THRESHOLD: 1000 ppm RESIDUALS AND IMPURITIES CONSIDERED: Partially						
	RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are partially considered.						
	OTHER PRODUCT NOTES: Helmice applications.	bl 3031 has been formulated to produce a s	superior, hard	setting bond req	uired for use in hi	igh traffic	
LIMESTONE ID:						ID: 1317-65-3	
	HAZARD SCREENING METHOD:	Pharos Chemical and Materials Library	HAZARD SC	REENING DATE:	2021-02-18		
	%: 30.0000 - 60.0000	GS: LT-UNK	RC: None	NANO: No	SUBSTANCE I	ROLE: Filler	
	HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS				
	None found			No warnings for	ound on HPD Pric	ority Hazard Lists	
	SUBSTANCE NOTES:						
	4-NONYLPHENOL (BRANCHED)					ID: 84852-15-3	
	HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2021-02-18				
	%: 10.0000 - 30.0000	GS: LT-1	RC: None	NANO: No	SUBSTANCE RC	DLE: Monomer	

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
AQU	EU - GHS (H-Statements)	H400 - Very toxic to aquatic life
AQU	EU - GHS (H-Statements)	H410 - Very toxic to aquatic life with long lasting effects
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
END	OSPAR - Priority PBTs & EDs & equivalent concern	Endocrine Disruptor - Chemical for Priority Action
MUL	US EPA - PPT Chemical Action Plans	EPA Chemical of Concern - Action Plan published
MUL	US EPA - PPT Chemical Action Plans	TSCA Work Plan chemical - Action Plan in development
END	ChemSec - SIN List	Endocrine Disruption
REP	US EPA - PPT Chemical Action Plans	Reproductive effects
AQU	US EPA - PPT Chemical Action Plans	Highly toxic to aquatic organisms
DEV	US EPA - PPT Chemical Action Plans	Developmental Effects
MUL	ChemSec - SIN List	CMR - Carcinogen, Mutagen &/or Reproductive Toxicant
MUL	German FEA - Substances Hazardous to Waters	Class 3 - Severe Hazard to Waters
SKI	EU - GHS (H-Statements)	H314 - Causes severe skin burns and eye damage
REP	EU - GHS (H-Statements)	H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child
PBT	OSPAR - Priority PBTs & EDs & equivalent concern	PBT - Substance of Possible Concern
PBT	ChemSec - SIN List	PBT / vPvB (Persistent, Bioaccumulative, & Toxic / very Persistent & very Bioaccumulative)
END	EU - SVHC Authorisation List	Equivalent Concern - Candidate List

SUBSTANCE NOTES:

DIAMINOPOLYPROPYLENE GL	YCOL				ID: 9046-10-0
HAZARD SCREENING METHOD	Pharos Chemical and Materials Library	HAZARD SC	CREENING DA	TE: 2021-02-18	
%: 10.0000 - 30.0000	GS: LT-P1	RC: None	NANO: No	SUBSTANCE RO	LE: Intermediate
HAZARD TYPE	AGENCY AND LIST TITLES	WAR	NINGS		
MUL	German FEA - Substances Hazardous t Waters	to Class	2 - Hazard to	Waters	
SUBSTANCE NOTES:					
N-(2-AMINOETHYL)PIPERAZINI	E				ID: 140-31-8
HAZARD SCREENING METHOD	Pharos Chemical and Materials Library	HAZARD SC	CREENING DA	TE: 2021-02-18	
%: 5.0000 - 10.0000	GS: LT-P1	RC: None	NANO: No	SUBSTANCE RO	LE: Intermediate

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
SKI	EU - GHS (H-Statements)	H314 - Causes severe skin burns and eye damage			
MUL	German FEA - Substances Hazardous t Waters	Class 2 - Hazard to Waters			
SKI	EU - GHS (H-Statements)	H317 - May cause an allergic skin reaction			
SUBSTANCE NOTES:					
SILICON DIOXIDE		ID: 7631-86-9			
HAZARD SCREENING METHOD:	Pharos Chemical and Materials Library	HAZARD SCREENING DATE: 2021-02-18			
%: 1.0000 - 5.0000	GS: BM-1	RC: None NANO: No SUBSTANCE ROLE: Filler			
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
CAN	GHS - Australia	H350i - May cause cancer by inhalation			
CAN	GHS - Japan	Carcinogenicity - Category 1A [H350]			
SUBSTANCE NOTES:					
1,4-BIS(AMINOCYCLOHEXYL)M	ETHANE	ID: 1761-71-3			
		HAZARD SCREENING DATE: 2021-02-18			
%: 1.0000 - 5.0000	GS: LT-P1	RC: None NANO: No SUBSTANCE ROLE: Intermediate			
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
MUL	German FEA - Substances Hazardous t Waters	to Class 3 - Severe Hazard to Waters			
SUBSTANCE NOTES:					

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	VOC Emissions		
CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: 11110 Airport Road Olive Branch MS 38654 CERTIFICATE URL:	ISSUE DATE: 2021-02- 22	EXPIRY DATE: 2022- 03-01	CERTIFIER OR LAB: Helmitin Inc.
CERTIFICATION AND COMPLIANCE NOTES: VOC <12g/L			
VOC CONTENT	VOC Content		
CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: 11110 Airport Road Olive Branch MS 38654 CERTIFICATE URL:	ISSUE DATE: 2021-02- 22	EXPIRY DATE: 2022- 03-01	CERTIFIER OR LAB: Helmitin Inc.
CERTIFICATION AND COMPLIANCE NOTES: VOC <12g/L			
MANAGEMENT	ISO 9001:2015 Quality management systems		
CERTIFYING PARTY: Third Party APPLICABLE FACILITIES: Helmitin - Olive Branch, MS CERTIFICATE URL:	ISSUE DATE: 2020-06- 21	EXPIRY DATE: 2023- 06-21	CERTIFIER OR LAB: SGS International
CERTIFICATION AND COMPLIANCE NOTES:			

😑 Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Helmicol 3031 can be used on porous and non-porous surfaces free of moisture. Surface to be covered must be dry, clean and smooth. Any foreign materials present such as paint, grease, oil, pen markings, adhesive residues, etc. that may prevent a proper bond must be removed. Adhesive can be used on all grades of concrete on, above or below grade in the absence of moisture. Concrete shall be prepared according to the recommendations outlined in ASTM F710 (Standard Practice for Preparing Concrete Floors to Receive Resilient Flooring). Concrete shall be free from crazing, dusting, spalling and any curing or sealing compounds. Concrete shall be tested for moisture according to the latest revision of ASTM F2170 (Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes) and ASTM F1869 (Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete Subfloor Using Anhydrous Calcium Chloride. Wood floors must be double construction with a 1" minimum thickness, structurally sound, securely fastened and free from deflection/spring. Top layer of wood shall be underlayment grade plywood. Cracks and uneven surfaces must be filled with an approved cement-based patching compound. STAIR TREAD APPLICATION: Cartridge adhesive automatically mixes when pumped through tip. Cut cartridge tip to desired width. Apply a sufficient amount of epoxy nose caulking into the inside nose area of the stair tread to completely fill the void between the nosing angle of the stair tread and the nosing of the stair step. Stair tread can be positioned immediately after adhesive application. The maximum adhesive open time is 10 minutes at 68°F (20°C). Higher temperatures will result in shorter open times. When positioning stair tread, make sure that the nosing of the stair tread is positioned tightly against the step nosing. When installing treads from the bottom working up, do not kneel or step of the nosing of the tread as this can cause displacement of the adhesive. Roll the tread and riser areas with a hand roller. Do not roll the nosing of the stair tread as this can cause displacement of the adhesive.

MANUFACTURER INFORMATION

MANUFACTURER: Helmitin Inc. ADDRESS: 11110 Airport Road Olive Branch Mississippi 38654, United States WEBSITE: http://www.helmitin.com

CONTACT NAME: Scott Holman TITLE: Director of Compliance & IT PHONE: 437-370-0042 EMAIL: s.holman@helmitin.com

LT-1 List Translator 1 (Likely Benchmark-1)

to a LT-1 or LTP1 score.)

NoGS No GreenScreen.

LT-UNK List Translator Benchmark Unknown (the chemical is

information contained within the list did not result in a clear mapping

present on at least one GreenScreen Specified List, but the

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity CAN Cancer DEV Developmental toxicity END Endocrine activity EYE Eye irritation/corrosivity GEN Gene mutation GLO Global warming LAN Land toxicity MAM Mammalian/systemic/organ toxicity MUL Multiple NEU Neurotoxicity NF Not found on Priority Hazard Lists OZO Ozone depletion PBT Persistent, bioaccumulative, and toxic PHY Physical hazard (flammable or reactive) REP Reproductive RES Respiratory sensitization SKI Skin sensitization/irritation/corrosivity UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)
BM-3 Benchmark 3 (use but still opportunity for improvement)
BM-2 Benchmark 2 (use but search for safer substitutes)
BM-1 Benchmark 1 (avoid - chemical of high concern)
BM-U Benchmark Unspecified (due to insufficient data)
LT-P1 List Translator Possible 1 (Possible Benchmark-1)

Recycled Types

PreC Pre-consumer recycled content PostC Post-consumer recycled content UNK Inclusion of recycled content is unknown None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology Third Party Verified Verification by independent certifier approved by HPDC Preparer Third party preparer, if not self-prepared by manufacturer Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.