

HPD UNIQUE IDENTIFIER: 29329

CLASSIFICATION: 09 29 00 Gypsum Board

PRODUCT DESCRIPTION: USG Sheetrock® Brand Mold Tough® VHI Firecode® X Panels have a noncombustible, moisture resistant core encased in moisture- and mold-resistant, 100 percent recycled green-face and brown-back papers. The face paper is folded around the long edges to reinforce and protect the core, and the ends are cut square and finished smooth. Through a proprietary process, a fiberglass reinforcing mesh is imbedded in the core adjacent to the back paper. This mesh strengthens the panels and increases resistance against impact damage. The long edges of panels are tapered, allowing joints to be reinforced and concealed with a USG joint treatment system.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

<p>Inventory Reporting Format</p> <p><input type="radio"/> Nested Materials Method</p> <p><input checked="" type="radio"/> Basic Method</p> <p>Threshold Disclosed Per</p> <p><input type="radio"/> Material</p> <p><input checked="" type="radio"/> Product</p>	<p>Threshold Level</p> <p><input type="radio"/> 100 ppm</p> <p><input checked="" type="radio"/> 1,000 ppm</p> <p><input type="radio"/> Per GHS SDS</p> <p><input type="radio"/> Other</p>	<p>Residuals/Impurities Evaluation</p> <p><input checked="" type="radio"/> Completed</p> <p><input type="radio"/> Partially Completed</p> <p><input type="radio"/> Not Completed</p> <p>Explanation(s) provided :</p> <p><input checked="" type="radio"/> Yes <input type="radio"/> No</p>	<p><i>For all contents above the threshold, the manufacturer has:</i></p> <p>Characterized <input checked="" type="radio"/> Yes <input type="radio"/> No</p> <p><i>Provided weight and role.</i></p> <p>Screened <input checked="" type="radio"/> Yes <input type="radio"/> No</p> <p><i>Provided screening results using HPDC-approved methods.</i></p> <p>Identified <input type="radio"/> Yes <input checked="" type="radio"/> No</p> <p><i>Provided name and CAS RN or other identifier.</i></p>
--	--	--	---

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

PRODUCT | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE
SHEETROCK® BRAND MOLD TOUGH® VHI FIRECODE® X PANELS [GYPSUM BM-3dg | | DEV | MAM CELLULOSE, MICROCRYSTALLINE LT-UNK | RES FLY ASH LT-UNK | SOLID GLASS AND GLASS / MINERAL FIBER (SEE VARIANTS) LT-UNK | | MUL UNDISCLOSED LT-UNK | | MUL]

Number of Greenscreen BM-4/BM3 contents ... 0
 Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... None
 Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Residuals/Impurities in raw materials that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS are displayed in the HPD when greater than or equal to 1000 ppm. USG uses an outside lab to quantify potential impurities of raw materials. Analytical methods may include but are not limited to; x-ray diffraction, x-ray fluorescence, atomic absorption, ion chromatography, liquid chromatography, and crystalline silica analysis.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Option 1.
 Pre-checked for LEED v4.1 Option 1.

Third Party Verified?

- Yes
- No

PREPARER: Self-Prepared

VERIFIER:
 VERIFICATION #:

SCREENING DATE: 2022-07-22

PUBLISHED DATE: 2022-07-22
 EXPIRY DATE: 2025-07-22

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

SHEETROCK® BRAND MOLD TOUGH® VHI FIRECODE® X PANELS

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

RESIDUALS AND IMPURITIES NOTES: Raw materials in this product may contain trace amounts of respirable crystalline silica. Testing has shown exposures to respirable crystalline silica are not expected to exceed the OSHA Permissible Exposure Level (PEL) during the normal use of this product. See the SDS on usg.com for occupational exposure information. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

OTHER PRODUCT NOTES: This product is made at Baltimore, MD, Jacksonville, FL, Plaster City, CA, Rainier, OR, Shoals, IN, and Sweetwater, TX. Percent ranges displayed for this HPD are for all manufacturing plants that make this product and may vary.

GYPSUM

ID: 13397-24-5

HAZARD DATA SOURCE: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2022-07-22 9:33:10

%: 82.0000 - 95.0000 GreenScreen: BM-3dg RC: PreC NANO: No SUBSTANCE ROLE: Structure component

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
	EC - CEPA DSL	Persistent
DEV	MAK	Pregnancy Risk Group C
MAM	GHS - Japan	H335 or H336 [Specific target organs/systemic toxicity following single exposure - Category 3]

ADDITIONAL LISTINGS	AGENCY AND LIST TITLES	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. The use of FGD gypsum and the pre-consumer recycled content of Sheetrock® Brand Mold Tough® VHI Firecode® X Panels will vary by the manufacturing plant.

CELLULOSE, MICROCRYSTALLINE

ID: 9004-34-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2022-07-22 9:33:11

%: 5.5000 - 7.0000 GreenScreen: LT-UNK RC: PostC NANO: No SUBSTANCE ROLE: Structure component

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
RES	AOEC - Asthmagens	Asthmagen (Rs) - sensitizer-induced

ADDITIONAL LISTINGS	AGENCY AND LIST TITLES	NOTIFICATION
EXEMPT	European Union / European Commission (EU EC)	EU - REACH Exemptions
POSITIVE LIST	US Environmental Protection Agency (US EPA)	US EPA - DfE SCIL

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

FLY ASH

ID: 68131-74-8

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-07-22 9:33:11		
%: 0.3000 - 0.8000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Catalyst
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
	EC - CEPA DSL	Persistent		
ADDITIONAL LISTINGS	AGENCY AND LIST TITLES	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

SOLID GLASS AND GLASS / MINERAL FIBER (SEE VARIANTS)

ID: 65997-17-3

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-07-22 9:33:12		
%: 0.3000 - 0.8000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Tensile strength additive
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
	EC - CEPA DSL	Persistent		
MUL	Québec CSST - WHMIS 1988	Class D2A - Very toxic material causing other toxic effects		
ADDITIONAL LISTINGS	AGENCY AND LIST TITLES	NOTIFICATION		
EXEMPT	European Union / European Commission (EU EC)	EU - REACH Exemptions		
POSITIVE LIST	US Environmental Protection Agency (US EPA)	US EPA - DfE SCIL		

SUBSTANCE NOTES: As manufactured, continuous filament glass fibers in this product are not respirable. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

UNDISCLOSED

ID: **Undisclosed**

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-07-22 9:33:12		
%: 0.2000 - 0.4000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Tensile strength additive

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
	EC - CEPA DSL	Persistent
MUL	German FEA - Substances Hazardous to Waters	Class 1 - Low Hazard to Waters
ADDITIONAL LISTINGS	AGENCY AND LIST TITLES	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Proprietary ingredient. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. Not on the Living Building Challenge™ (LBC) Red List Chemical Guide (Version 3.1)

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

UL/GreenGuard Gold Certified

CERTIFYING PARTY: Third Party
APPLICABLE FACILITIES: All
CERTIFICATE URL: <https://spot.ul.com/>

ISSUE DATE: 2016-01-29
EXPIRY DATE:

CERTIFIER OR LAB: UL
Environment

CERTIFICATION AND COMPLIANCE NOTES: Building products and interior finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office and Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m³) fall in the range of 0.5 mg/m³ or less, as specified in CDPH Standard Method v1.2.

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

USG SHEETROCK® OR BEADEX® BRAND FINISHING PRODUCTS

MANUFACTURER (OR GENERIC): USG

HPD URL: <https://www.usg.com>

ACCESSORY TYPE:

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: Building products and interior finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office and Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m³) fall in the range of 0.5 mg/m³ or less, as specified in CDPH Standard Method v1.2.

Section 5: General Notes

The International Agency for Research on Cancer (IARC) in June, 1987, categorized continuous filament glass fibers as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify continuous filament glass fiber as a possible, probable, or confirmed cancer causing material.

MANUFACTURER INFORMATION

MANUFACTURER: USG
ADDRESS: 550 West Adams St
 Chicago IL 60661, United States
WEBSITE: usg.com

CONTACT NAME: Stacy Simpson
TITLE: Sustainability Manager
PHONE: 1-800-USG4YOU
EMAIL: sustainability@usg.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

- PreC** Pre-consumer recycled content
- PostC** Post-consumer recycled content
- UNK** Inclusion of recycled content is unknown
- None** Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

- Nested Method / Material Threshold** Substances listed within each material per threshold indicated per material
- Nested Method / Product Threshold** Substances listed within each material per threshold indicated per product
- Basic Method / Product Threshold** Substances listed individually per threshold indicated per product

- Nano** Composed of nano scale particles or nanotechnology
- Third Party Verified** Verification by independent certifier approved by HPDC
- Preparer** Third party preparer, if not self-prepared by manufacturer
- Applicable facilities** Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.