Aussie Membrane 520-PRO (Polyurethane) by AVM Industries

SCREENING DATE: 2026-08-18
PUBLISHED DATE: 2026-08-18
EXPIRY DATE: 2029-08-18
PREPARER: Self-Prepared

Health Product Declaration v3.0
created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 20838935
HPD UNIQUE PRODUCT ID: Not provided.
CLASSIFICATION: 07 14 00 Fluid-Applied Waterproofing
PRODUCT TYPE: Fluid Applied Waterproofing, Cold Applied
Fluid Applied Flooring, Polyurethane
PRODUCT DESCRIPTION: Aussie Membrane 520-PRO is a single-component, cold-applied polyurethane liquid waterproofing membrane designed to cure into a seamless, flexible waterproofing membrane. It is primarily used for below-grade waterproofing applications.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format
→ Basic Method

Threshold Disclosed Per
→ Product

Threshold Level
→ Per GHS SDS

Residuals/Impurities Evaluation
→ Not Completed

Explanation(s) provided :
Yes

For all contents above the threshold, the manufacturer has:

Characterized Yes
Provided weight and role.

Screened No
Provided screening results using HPDC-approved methods.

Identified No
Provided name and CAS RN or other identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

PRODUCT | **MATERIAL OR SUBSTANCE** | *RESIDUAL OR IMPURITY*
GREENSCREEN SCORE | HAZARD TYPE

AUSSIE MEMBRANE 520-PRO (POLYURETHANE) [PROPRIETARY POLYURETHANE MEMBRANE COMPONENTS Not Screened **BIS(2-ETHYLHEXYL) 2-ETHYLHEXYLPHOSPHONATE** NoGS **]**

Number of Greenscreen BM-4/BM3 contents ... 0
Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... None
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Special Conditions applied: [GeologicalMaterial]

Product content disclosure is based on available manufacturer, supplier, and Safety Data Sheet information. Chemical identities and concentrations are reported to the extent disclosed in the applicable SDS. Certain formulation information may be proprietary or withheld as trade secret.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 75 Regulatory (g/l): <250
Does the product contain exempt VOCs: No
Are colorants available that do not increase the VOC content of the base paint when tinted: N/A

COMPLIANCE *See Section 3 for additional listings.*

VOC emissions: CDPH Standard Method - Not tested
VOC content: SCAQMD Rule 1113 Architectural Coatings - Concrete curing compounds, Industrial Maintenance (IM) Coatings, Zinc-Rich IM Primers, Primers, Sealers, and Undercoaters, including Quick-Dry Primers, Sealers, and Undercoaters and Specialty Primers, Rust Prevent

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed.

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- *Basic Inventory method with Product-level threshold.*
- *Nested Material Inventory method with Product-level threshold*
- *Nested Material Inventory method with individual Material-level thresholds*

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 3.0, available on the HPDC website at: www.hpd-collaborative.org/hpd-3-0-standard

AUSSIE MEMBRANE 520-PRO (POLYURETHANE)

PRODUCT THRESHOLD: Per GHS SDS

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities have not been independently evaluated. Product content is reported based on available manufacturer, supplier, and Safety Data Sheet information.

OTHER PRODUCT NOTES: Aussie Membrane 520-PRO is a single-component, cold-applied polyurethane waterproofing membrane. Product content disclosure is based on available manufacturer and supplier documentation.

PROPRIETARY POLYURETHANE MEMBRANE COMPONENTS

ID: **Unknown**

HAZARD DATA SOURCE: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **Not Screened**

%: **80.0000 - 80.0000** GreenScreen: **Not Screened** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
	Hazard Screening not performed	

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
	Additional Hazard Screening not performed	

SUBSTANCE NOTES: Represents the balance of the proprietary polyurethane membrane formulation not specifically identified in the applicable Safety Data Sheet. Individual chemical identities and concentrations are not available from current manufacturer and supplier documentation.

BIS(2-ETHYLHEXYL) 2-ETHYLHEXYLPHOSPHONATE

ID: **126-63-6**

HAZARD DATA SOURCE: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2026-08-18 14:19:27**

%: **10.0000 - 30.0000** GreenScreen: **NoGS** RC: **None** NANO: **No** SUBSTANCE ROLE: **Corrosion inhibitor**

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Concentration range and chemical identity reported per the applicable Safety Data Sheet. Exact concentration is withheld as trade secret.

Section 3: Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS — **CDPH Standard Method - Not tested**

COMPLIANCE TYPE: Self-declaration
CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: None
COMPLIANCE DETAILS:
COMPLIANCE SCOPE: Product
APPLICABLE FACILITIES: China
COMPLIANCE URL:
COMPLIANCE NOTES: Aussie Membrane 520-PRO has not been tested or certified for VOC emissions. The product is a liquid-applied polyurethane waterproofing membrane with a reported VOC content of 75 g/L. No VOC emissions certification is currently available for this product.

ISSUE DATE: 2026-08-18

EXPIRY DATE: No expiration

VOC CONTENT — **SCAQMD Rule 1113 Architectural Coatings - Concrete curing compounds, Industrial Maintenance (IM) Coatings, Zinc-Rich IM Primers, Primers, Sealers, and Undercoaters, including Quick-Dry Primers, Sealers, and Undercoaters and Specialty Primers, Rust Prevent**

COMPLIANCE TYPE: Self-declaration
CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: unknown
COMPLIANCE DETAILS:
COMPLIANCE SCOPE: Product
APPLICABLE FACILITIES: China
COMPLIANCE URL:
COMPLIANCE NOTES: Aussie Membrane 520-PRO is a liquid-applied polyurethane waterproofing membrane used in below-grade, plaza deck, and traffic coating applications. The product has a reported VOC content of 75 g/L based on manufacturer product documentation. No independent third-party VOC content certification has been performed.

ISSUE DATE: 2026-08-18

EXPIRY DATE: No expiration

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Aussie Membrane 520-PRO is a single-component, cold-applied polyurethane waterproofing membrane. Product content information is based on available manufacturer, supplier, Technical Data Sheet, and Safety Data Sheet information. Chemical identities and concentrations are reported to the extent disclosed in the applicable SDS. Certain components of the proprietary formulation are not individually identified in the available SDS and are reported as unknown proprietary components. The product has a reported VOC content of 75 g/L.

Section 6: References

MANUFACTURER INFORMATION

MANUFACTURER: **AVM Industries**
ADDRESS: **8245 Remmet Ave**
Canoga Park, CA 91304
COUNTRY: **United States**

WEBSITE: **www.avmindustries.com**
CONTACT NAME: **Mitch Buchanan**
TITLE: **Technical Services Manager**
PHONE: **815-355-8275**
EMAIL: **mitch@avmindustries.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity
CAN Cancer
DEV Developmental toxicity
END Endocrine activity
EYE Eye irritation/corrosivity
GEN Gene mutation
GLO Global warming
LAN Land toxicity
MAM Mammalian/systemic/organ toxicity
MUL Multiple
NEU Neurotoxicity
NF Not found on Priority Hazard Lists
OZO Ozone depletion
PBT Persistent, bioaccumulative, and toxic
PHY Physical hazard (flammable or reactive)
REP Reproductive
RES Respiratory sensitization
SKI Skin sensitization/irritation/corrosivity
UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)
BM-3 Benchmark 3 (use but still opportunity for improvement)
BM-2 Benchmark 2 (use but search for safer substitutes)
BM-1 Benchmark 1 (avoid - chemical of high concern)
BM-U Benchmark Unspecified (due to insufficient data)
LT-P1 List Translator Possible 1 (Possible Benchmark-1)
LT-1 List Translator 1 (Likely Benchmark-1)
LT-UNK List Translator Benchmark Unknown
NoGS No GreenScreen.

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.