790-11EV Hot Rubberized Asphalt by Henry Company

CLASSIFICATION: 07 14 13.00

PRODUCT DESCRIPTION: 790-11EV is an environmentally friendly, hot applied, rubberized asphalt formulated to provide a monolithic fully bonded roofing and waterproofing membrane. It is hot poured in a single or fabric reinforced application. 790-11 EV is composed of a specially selected blend of refined asphalts, synthetic rubber and mineral stabilizers and contains at least 25% post consumer recycled content. It is modified with additives to promote adhesion and improve low temperature flexibility.

Section 1: Summary

CONTENT INVENTORY

Inventory Reporting Format

Nested Materials Method
 Basic Method

Threshold Disclosed Per

- C Material
- Product

Threshold level

C 1,000 ppm C Per GHS SDS C Per OSHA MSDS C Other

Residuals/Impurities

- Considered
 Partially Considered
 Not Considered
- Explanation(s) provided for Residuals/Impurities?

All Substances Above the Threshold Indicated Are:

Basic Method / Product Threshold

Characterized C Yes Ex/SC • Yes C No % weight and role provided for all substances.

Screened O Yes Ex/SC O Yes O No All substances screened using Priority Hazard Lists with results disclosed.

Identified O Yes Ex/SC O Yes O No All substances disclosed by Name (Specific or Generic) and Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | *RESIDUAL OR IMPURITY* GREENSCREEN SCORE | HAZARD TYPE

790-11 HOT RUBBERIZED ASPHALT [ASPHALT LT-1 | CAN LIMESTONE; CALCIUM CARBONATE LT-UNK SOLVENT-DEWAXED HEAVY PARAFFINIC PETROLEUM DISTILLATES LT-1 | CAN | MUL STYRENE BUTADIENE RUBBER (SBR) LT-UNK *QUARTZ* LT-1 | CAN *SULFUR* LT-UNK | SKI]

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 0.0 Regulatory (g/l): 0.0 Does the product contain exempt VOCs: No Are ultra-low VOC tints available: N/A Number of Greenscreen BM-4/BM3 contents ... 0 Contents highest concern GreenScreen Benchmark or List translator Score ... LT-1 Nanomaterial ... No INVENTORY AND SCREENING NOTES: None

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings. VOC emissions: Self-declared VOC content: EPA Method 24 - Volatile Matter Content (EPA 24)

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

hpdrepository.hpd-collaborative.org

O Yes No PREPARER: Self-Prepared VERIFIER: VERIFICATION #: SCREENING DATE: 2020-04-14 PUBLISHED DATE: 2020-04-14 EXPIRY DATE: 2023-04-14

Health Product Declaration v2.1.1

created via: HPDC Online Builder

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

790-11 HOT RUBBERIZED ASPHALT

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities considered

OTHER PRODUCT NOTES: None

ASPHALT ID: 8052-42-4 HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2020-04-14 GS: LT-1 %: 35.00 - 55.00 RC: None NANO: **NO** ROLE: Membrane layer HAZARD TYPE AGENCY AND LIST TITLES WARNINGS CANCER IARC Group 2b - Possibly carcinogenic to humans CANCER US CDC - Occupational Carcinogens **Occupational Carcinogen** CANCER CA EPA - Prop 65 Carcinogen CANCER IARC Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources CANCER MAK Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification

SUBSTANCE NOTES: This is not used for road paving applications so it is not considered a carcinogen by IARC.

LIMESTONE; CALCIUM CARBONATE					
HAZARD SCREENING METHOD: P	HAZARD SCREENING DATE: 2020-04-14				
%: 30.00 - 40.00	GS: LT-UNK	RC: None	NANO: NO	ROLE: Filler/Film strengthener	
HAZARD TYPE	AGENCY AND LIST TITLES	WAR	NINGS		
None found			No war	nings found on HPD Priority Hazard Lists	
SUBSTANCE NOTES: Not in respirable form					

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2020-04-14			
%: 10.00 - 20.00	GS: LT-1	RC: PostC NANO: No ROLE: Flexibility			
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
CANCER	EU - GHS (H-Statements)	H350 - May cause cancer			
CANCER	EU - REACH Annex XVII CMRs	Carcinogen Category 2 - Substances which should be regarded as if they are Carcinogenic to man			
MULTIPLE	ChemSec - SIN List	CMR - Carcinogen, Mutagen &/or Reproductive Toxicant			
CANCER	EU - Annex VI CMRs	Carcinogen Category 1B - Presumed Carcinogen based on animal evidence			
CANCER	GHS - Australia	H350 - May cause cancer			

SUBSTANCE NOTES: Contains less than 3% DMSO extractables - not considered a carcinogen or mutagen.

STYRENE BUTADIENE R	UBBER (SBR)			ID: 9003-5
HAZARD SCREENING METHOD:	Pharos Chemical and Materials Library	HAZARD SCREEN	NG DATE: 2020-04	l-14
%: 5.00 - 15.00	GS: LT-UNK	RC: PostC	NANO: NO	ROLE: Flexibility
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No	warnings found o	on HPD Priority Hazard Lis
SUBSTANCE NOTES: None				

QUARTZ				ID: 14808-60-7
HAZARD SCREENING METHOD: Pharos (HAZARD SCREENING DATE: 2020-04-14			
%: Impurity/Residual	GS: LT-1	RC: None	NANO: NO	ROLE: Impurity/Residual

GS: LT-1

RC: None

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	US CDC - Occupational Carcinogens	Occupational Carcinogen
CANCER	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CANCER	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CANCER	МАК	Carcinogen Group 1 - Substances that cause cancer in man
CANCER	IARC	Group 1 - Agent is Carcinogenic to humans
CANCER	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CANCER	GHS - New Zealand	6.7A - Known or presumed human carcinogens
CANCER	GHS - Japan	Carcinogenicity - Category 1A [H350]
CANCER	GHS - Australia	H350i - May cause cancer by inhalation

SUBSTANCE NOTES: This substance is encapsulated in the membrane.

SULFUR				ID: 7704-34-9
HAZARD SCREENING METHOD: Pha	HAZARD SCREENING DATE: 2020-04-14			
%: Impurity/Residual	GS: LT-UNK	RC: None	NANO: NO	ROLE: Impurity/Residual
HAZARD TYPE	AGENCY AND LIST TITLES	WARNING	GS	
SKIN IRRITATION	EU - GHS (H-Statements)	H315 - Causes skin irritation		tation

SUBSTANCE NOTES: None

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	Self-declared					
CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: All Henry facilities CERTIFICATE URL:	ISSUE DATE: 2020- 04-14	EXPIRY DATE:	CERTIFIER OR LAB: Henry Company			
CERTIFICATION AND COMPLIANCE NOTES: Exterior use only						
VOC CONTENT	EPA Method 24 - Volatile Matter Content (EPA 24)					
CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: All Henry facilities CERTIFICATE URL:	ISSUE DATE: 2020- 04-14	EXPIRY DATE:	CERTIFIER OR LAB: Henry Company			

CERTIFICATION AND COMPLIANCE NOTES: Exterior use only product

General Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

No additional general notes for this product.

MANUFACTURER INFORMATION

MANUFACTURER: Henry Company ADDRESS: 999 N. Pacific Coast Hwy Suite 800 El Segundo CA 90245, USA WEBSITE: www.henry.com CONTACT NAME: Whitney Randall TITLE: Director, Regulatory Compliance Systems PHONE: 484-557-1247 EMAIL: wrandall@henry.com

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

GLO Global warming

MUL Multiple hazards

OZO Ozone depletion

NEU Neurotoxicity

MAM Mammalian/systemic/organ toxicity

PBT Persistent Bioaccumulative Toxic

Hazard Types

AQU Aquatic toxicity CAN Cancer DEV Developmental toxicity END Endocrine activity EYE Eye irritation/corrosivity GEN Gene mutation

ion/corrosivity tation

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)
BM-3 Benchmark 3 (use but still opportunity for improvement)
BM-2 Benchmark 2 (use but search for safer substitutes)
BM-1 Benchmark 1 (avoid - chemical of high concern)
BM-U Benchmark Unspecified (insuficient data to benchmark)

PHY Physical Hazard (reactive) REP Reproductive toxicity RES Respiratory sensitization SKI Skin sensitization/irritation/corrosivity LAN Land Toxicity NF Not found on Priority Hazard Lists

LT-P1 List Translator Possible Benchmark 1 LT-1 List Translator Likely Benchmark 1 LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark) NoGS Unknown (no data on List Translator Lists)

Recycled Types

PreC Preconsumer (Post-Industrial) PostC Postconsumer Both Both Preconsumer and Postconsumer Unk Inclusion of recycled content is unknown None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology Third Party Verified Verification by independent certifier approved by HPDC Preparer Third party preparer, if not self-prepared by manufacturer Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.

790-11EV Hot Rubberized Asphalt hpdrepository.hpd-collaborative.org