ThermoCon® FC-TR Acoustical System by International Cellulose Corporation

Health Product Declaration v2.1.1

created via: HPDC Online Builder

CLASSIFICATION: 09 83 00 Finishes: Acoustic Finishes

PRODUCT DESCRIPTION: ThermoCon® FC-TR is a high-performance, acoustical finish system that is tailored to meet the acoustic, lighting and design objectives for a wide range of project types. ThermoCon® FC-TR is spray-applied to common substrates and can adhere to virtually any surface configuration, including domes. Made in the USA from recycled, plant-based fibers, ThermoCon® FC-TR is the natural choice for new construction, renovation and historic preservation projects. With one application, ThermoCon® FC-TR provides multiple performance properties - reducing installation time and the need for excessive building materials.



Section 1: Summary

Nested Method / Material Threshold

CONTENT INVENTORY

Inventory Reporting Format

Nested Materials Method

C Basic Method

Threshold Disclosed Per

Material

C Product

UNK]

Threshold level

C 100 ppm

1,000 ppm

Per GHS SDS Per OSHA MSDS

C Other

Residuals/Impurities

Residuals/Impurities Considered in 3 of 3 Materials

Explanation(s) provided for Residuals/Impurities?

Yes ○ No.

All Substances Above the Threshold Indicated Are:

Characterized

% weight and role provided for all substances except SC substances characterized according to SC guidance.

Screened

• Yes Ex/SC • Yes • No

All substances screened using Priority Hazard Lists with results disclosed except SC substances screened according to SC guidance.

Identified

O Yes Ex/SC O Yes ⊙ No

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SONAKRETE ADHESIVE [WATER BM-4 UNDISCLOSED LT-UNK POLY(VINYL ALCOHOL) LT-UNK] THERMOCON® FC-TR TREATED CELLULOSE FIBER INSULATION [SC:MIXED RECYCLED PAPER Not Screened BORIC ACID LT-1 | END | REP | MUL | DEL SODIUM TETRABORATE PENTAHYDRATE LT-1 | REP | MUL HYDROTREATED HEAVY PARAFFINIC PETROLEUM DISTILLATES (MINERAL OIL), CONTAINING LESS THAN 3% DMSO AS MEASURED BY IP 346 LT-UNK FERRIC OXIDE BM-2 | CAN] SK-2000 ADDITIVE [WATER BM-4 2-PROPENOIC ACID, TELOMER WITH SODIUM HYDROGEN SULFITE LT- Number of Greenscreen BM-4/BM3 contents ... 2

Contents highest concern GreenScreen

Benchmark or List translator Score ... LT-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Special conditions applied: MixedRecycledContent

[LEED v4] "Yes ex/SC" result is due only to materials and substances for which Special Conditions were applied. Thus "Yes ex/SC" does not disqualify the product for the LEED v4 Materials and Resources Disclosure and Optimization credit, Option 1.

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.1.1, and discloses hazards associated with all substances present at or above 1000 parts per million (ppm) in the finished product, along with the role and percent weight. Substances not "Identified" are those considered proprietary to suppliers.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 0 g/l Regulatory (g/l): 0 g/l Does the product contain exempt VOCs: No Are ultra-low VOC tints available: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified

VOC content: ASTM D3960 VOC content: ASTM D3960

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

C Yes

No

PREPARER: Self-Prepared VERIFIER: VERIFICATION #:

SCREENING DATE: 2019-08-08 PUBLISHED DATE: 2019-08-08 EXPIRY DATE: 2022-08-08



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

SONAKRETE ADHESIVE

%: 76.20 - 77.70

MATERIAL THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities were "Considered", as outlined in Emerging Best Practices. No residuals or impurities are known or expected to be present at or above the Content Inventory Threshold indicated that have a GS score of BM-1, LT-1, LT-P1 or NoGS based on information provided in supplier disclosure letters, supplier SDS, and as predicted by process chemistry (Pharos CML).

OTHER MATERIAL NOTES: Standard diluted adhesive mixture.

WATER 1D: 7732-18-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-08-08		
%: 94.90 - 95.40	GS: BM-4	RC: None	nano: No	ROLE: Diluent
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No	warnings found or	HPD Priority Hazard Lists

SUBSTANCE NOTES: GreenScreen Benchmark® assessment score of BM-4 was provided by the HPD Builder Tool.

UNDISCLOSED

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-08-08		
%: 2.60 - 3.10	GS: LT-UNK	RC: None	nano: No	ROLE: Binder
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No w	arnings found on H	HPD Priority Hazard Lists

SUBSTANCE NOTES: Supplier has disclosed substance name and CASRN under confidentiality agreement; substance to remain proprietary to Supplier. However, all known hazards have been disclosed.

POLY(VINYL ALCOHOL) ID: 9002-89-5

%: 1.90 - 2.00				
	gs: LT-UNK	RC: None	NANO: No	ROLE: Binder
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No wai	nings found on H	PD Priority Hazard Lists

SUBSTANCE NOTES: Identified on the US EPA Safer Chemical Ingredient List.

THERMOCON® FC-TR TREATED CELLULOSE FIBER INSULATION

%: 22.30 - 22.30

MATERIAL THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities were "Considered", as outlined in Emerging Best Practices. No residuals or impurities are known or expected to be present at or above the Content Inventory Threshold indicated that have a GS score of BM-1, LT-1, LT-P1 or NoGS based on information provided in supplier disclosure letters, supplier SDS, and as predicted by process chemistry (Pharos CML).

OTHER MATERIAL NOTES: Treated Cellulose Fiber Insulation mixed with diluted adhesive and additive (when applicable) prior to application.

SC:MIXED RECYCLED PAPER ID: SC:MixedRC

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-08-08		
%: 79.00 - 84.50	GS: Not Screened	RC: PreC	nano: No	ROLE: Insulation
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
	Hazard Screening not performed			

SUBSTANCE NOTES:

BORIC ACID

Version: SCMixedRC/2018-02-23

Is regular, analytical testing performed on the substance?: No BatchVariation: Inherent variation due to various paper sources

SourceofOrigin: No Entry

Why is there limited information?: No Entry

This disclosure does not provide information on the potential presence of hazardous substances which may be found in certain mixed recycled materials.

Includes pre-consumer recycled material from multiple sources, as confirmed by our Supplier. Efforts are underway to obtain certification of recycled content.

HAZARD SCREENING METHOD: Pharos	Chemical and Materials Library	HAZARD SCREENING DATE: 2019-08-08			
%: 12.00 - 15.00	GS: LT-1	RC: None	NANO: No	ROLE: Fire retardant; Anti-microbial	
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS		
ENDOCRINE	EU - Priority Endocrine Disruptors		Category 1 - In Activity	vivo evidence of Endocrine Disruption	
REPRODUCTIVE	EU - SVHC Authorisation List		Toxic to reproc	luction - Candidate list	
REPRODUCTIVE	EU - SVHC Authorisation List		Toxic to reproc	luction - Prioritized for listing	
REPRODUCTIVE	EU - GHS (H-Statements)		H360FD - May damage fertility. May damage the unbo		
MULTIPLE	ChemSec - SIN List		CMR - Carcino	gen, Mutagen &/or Reproductive Toxicant	
ENDOCRINE	TEDX - Potential Endocrine Disrupto	ors	Potential Endocrine Disruptor		
DEVELOPMENTAL	MAK		Pregnancy Risk Group B		
REPRODUCTIVE	EU - Annex VI CMRs		Reproductive Toxicity - Category 1B		
REPRODUCTIVE	GHS - Japan		Toxic to reproc	luction - Category 1B	
REPRODUCTIVE	GHS - Australia		H360Fd - May unborn child	damage fertility. Suspected of damaging the	

SUBSTANCE NOTES: Borate-treated cellulose insulation was tested for purposes of hazard classification under the Occupational Safety and Health Administration's 2012 Hazard Communication Standard. In a study conducted under OECD Guideline 414, there were no developmental effects in rats exposed to up to 270 mg/m3 (the highest exposure tested). In workers chronically exposed to high levels of borates for several years by way of inhalation, food, and drinking water, there was a clear absence of any reproductive effects. For boric acid and substantially similar mixtures (specifically, sodium tetraborate pentahydrate and sodium tetraborate decahydrate), the reproductive toxicity is substantially equivalent; therefore, the same hazard category (i.e., no classification for reproductive toxicity) may be applied.

ID: 10043-35-3

HAZARD SCREENING METHOD: Ph	aros Chemical and Materials Library	HAZARD SCREENING DATE: 2019-08-08			
%: 2.50 - 5.00	GS: LT-1	RC: None	nano: No	ROLE: Fire-retardant; Anti-microbial	
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS		
REPRODUCTIVE	EU - SVHC Authorisation List	Toxic to reproduction - Candidate list			
REPRODUCTIVE	EU - SVHC Authorisation List	Toxic to reproduction - Prioritized for listing			
REPRODUCTIVE	EU - GHS (H-Statements)	H360FD - May damage fertility. May damage the unborchild			
MULTIPLE	ChemSec - SIN List		CMR - Carcinogen, Mutagen &/or Reproductive Toxican		
REPRODUCTIVE	GHS - Japan	Toxic to reproduction - Category 1B			
REPRODUCTIVE	GHS - Australia	H360Fd - May damage fertility. Suspected of damaging unborn child			

SUBSTANCE NOTES: Borate-treated cellulose insulation was tested for purposes of hazard classification under the Occupational Safety and Health Administration's 2012 Hazard Communication Standard. In a study conducted under OECD Guideline 414, there were no developmental effects in rats exposed to up to 270 mg/m3 (the highest exposure tested). In workers chronically exposed to high levels of borates for several years by way of inhalation, food, and drinking water, there was a clear absence of any reproductive effects. For boric acid and substantially similar mixtures (specifically, sodium tetraborate pentahydrate and sodium tetraborate decahydrate), the reproductive toxicity is substantially equivalent; therefore, the same hazard category (i.e., no classification for reproductive toxicity) may be applied.

HYDROTREATED HEAVY PARAFFINIC PETROLEUM DISTILLATES (MINERAL OIL), CONTAINING LESS THAN 3% DMSO AS MEASURED BY IP 346

ID: 64742-54-7

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library				SCREENING D	ATE: 2019-08-08
%: 0.10 - 0.90	gs: LT-UNK		RC: None	NANO: No	ROLE: De-Dusting Oil
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found		N	o warnings fou	ind on HPD	Priority Hazard Lists
SUBSTANCE NOTES: Suppl	lier has confirmed DMSO <0.1% as per IP 34	16.			

FERRIC OXIDE ID: 1309-						
HAZARD SCREENING METHOD:	Pharos Chemical and Materials Library	HAZARD SCREEN	NING DATE: 2019-08	3-08		
%: 0.00 - 0.14	GS: BM-2	RC: None	nano: No	ROLE: Pigment		
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS				
CANCER	MAK	Carcinogen Group 3B - Evidence of carcinogeni but not sufficient for classification		•		

SUBSTANCE NOTES: Percent range given due to presence/absence of this substance in the various colors available. GreenScreen Benchmark® assessment score of BM-2 was provided by the HPD Builder Tool.

SK-2000 ADDITIVE

%: 0.00 - 1.50

MATERIAL THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities were "Considered", as outlined in Emerging Best Practices. No residuals or impurities are known or expected to be present at or above the Content Inventory Threshold indicated that have a GS score of BM-1, LT-1, LT-P1 or NoGS based on information provided in supplier disclosure letters, supplier SDS, and as predicted by process chemistry (Pharos CML).

OTHER MATERIAL NOTES: Optional optical additive used in darker colored systems.

WATER				ID: 7732-18 -
HAZARD SCREENING METHOD: P	Pharos Chemical and Materials Library	HAZARD SCREEN	IING DATE: 2019-08 -	.08
%: 51.00 - 53.00	GS: BM-4	RC: None	nano: No	ROLE: Diluent
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No	warnings found or	HPD Priority Hazard Lists

SUBSTANCE NOTES: GreenScreen Benchmark® assessment score of BM-4 was provided by the HPD Builder Tool.

2-PROPENOIC ACID, TELOMER WITH SODIUM HYDROGEN SULFITE

ID: 66019-18-9

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREE	HAZARD SCREENING DATE: 2019-08-08		
%: 47.00 - 49.00	GS: LT-UNK	RC: None	nano: No	ROLE: Optical Enhancer	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found			No warnings t	found on HPD Priority Hazard Lists	

SUBSTANCE NOTES: Identified on the US EPA Safer Chemical Ingredient List.



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

UL/GreenGuard Gold Certified

CERTIFYING PARTY: Third Party

ISSUE DATE: 2018-

EXPIRY DATE: 2020-

CERTIFIER OR LAB: UL

APPLICABLE FACILITIES: Houston, TX 77045 USA

12-11

07-05

Environment

CERTIFICATE URL:

http://certificates.ulenvironment.com/default.aspx?

id=133542&t=cs

CERTIFICATION AND COMPLIANCE NOTES: Certificate Number: 133542-420. UL 2818 - 2013 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings. Building products and interior finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using a 32m3 Room Environment. Wall finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using a Classroom Environment with an air change of 0.82 hr-1 and a loading of 94.60 m2. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2.

VOC CONTENT

ASTM D3960

CERTIFYING PARTY: Self-declared

ISSUE DATE: 2008-

EXPIRY DATE:

CERTIFIER OR LAB: Intertek

APPLICABLE FACILITIES: Houston, TX 77045 USA

07-31

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: ASTM D3960: Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings. Products tested: SonaKrete Adhesive Concentrate. Final Test Result: 0 g/L VOC.

VOC CONTENT

ASTM D3960

CERTIFYING PARTY: Self-declared

ISSUE DATE: 2008-

EXPIRY DATE:

CERTIFIER OR LAB: Intertek

APPLICABLE FACILITIES: Houston, TX 77045 USA

07-31

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: ASTM D3960: Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings. Products tested: SK-2000 Additive Concentrate. Final Test Result: 0 g/L VOC.



Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.



Section 5: General Notes

MANUFACTURER INFORMATION

MANUFACTURER: International Cellulose Corporation

ADDRESS: 12315 Robin Blvd. Houston TX 77045, USA

WEBSITE: www.spray-on.com

CONTACT NAME: Lauren Kempe

TITLE: Architectural Sales Representative

PHONE: (713) 610-4731

EMAIL: Ikempe@spray-on.com

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity

CAN Cancer **DEV** Developmental toxicity **END** Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

MAM Mammalian/systemic/organ toxicity

MUL Multiple hazards

NEU Neurotoxicity **OZO** Ozone depletion

PBT Persistent Bioaccumulative Toxic

PHY Physical Hazard (reactive) **REP** Reproductive toxicity

RES Respiratory sensitization SKI Skin sensitization/irritation/corrosivity

LAN Land Toxicity

NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insuficient data to benchmark)

LT-P1 List Translator Possible Benchmark 1 LT-1 List Translator Likely Benchmark 1

LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark) NoGS Unknown (no data on List Translator Lists)

Recycled Types

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

Both Both Preconsumer and Postconsumer Unk Inclusion of recycled content is unknown None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.