

CLASSIFICATION: 09 91 13

PRODUCT DESCRIPTION: AcryShield is a family of premium quality exterior paints, enamels and primers designed for excellent weathering and a lasting impression. Created with a 100% acrylic formula to provide outstanding color and gloss retention. AcryShield is backed by the confidence of Kelly-Moore's Lifetime Warranty. This product is designed for use on walls and accents.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
 Basic Method

Threshold Disclosed Per

- Material
 Product

Threshold level

- 100 ppm
 1,000 ppm
 Per GHS SDS
 Per OSHA MSDS
 Other

Residuals/Impurities

- Considered
 Partially Considered
 Not Considered

Explanation(s) provided for Residuals/Impurities?

- Yes No

All Substances Above the Threshold Indicated Are:

Characterized Yes Ex/SC Yes No
% weight and role provided for all substances.

Screened Yes Ex/SC Yes No
All substances screened using Priority Hazard Lists with results disclosed.

Identified Yes Ex/SC Yes No
All substances disclosed by Name (Specific or Generic) and Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE

1240 ACRYSHIELD EXTERIOR FLAT PAINT [WATER BM-4 POLYMETHYL METHACRYLATE (PMMA) LT-P1 | RES NEPHELINE SYENITE LT-UNK DIATOMACEOUS EARTH [WHICH CONTAINS LESS THAN 0.1% OF CRYSTALLINE SILICA] LT-UNK SOLVENT-DEWAXED HEAVY PARAFFINIC PETROLEUM DISTILLATES LT-1 | CAN | MUL 1,3-PENTANEDIOL, 2,2,4-TRIMETHYL-, MONOISOBUTYRATE LT-UNK | CAN 3(2H)-ISOTHIAZOLONE, 4,5-DICHLORO-2-OCTYL- BM-2 | END | MUL 2,2'-ETHYLENEDIOXYDIETHYL BIS(2-ETHYLHEXANOATE) LT-UNK AMMONIA LT-P1 | RES | AQU | SKI | MAM | END | MUL 1,2-BENZISOTHIAZOLIN-3-ONE (BIT) LT-P1 | AQU | SKI | EYE | MUL POLOXANLENE LT-UNK HYDROXYETHYL CELLULOSE LT-P1 | END HECTORITE LT-UNK POLY(OXY-1,2-ETHANEDIYL), ALPHA-TRIDECYL-OMEGA-HYDROXY-, PHOSPHATE, POTASSIUM SALT LT-UNK POLYETHYLENE GLYCOL LT-UNK 2-PROPENOIC ACID, POLYMER WITH ETHENYLBENZENE LT-UNK TITANIUM DIOXIDE LT-1 | CAN | END TALC BM-1 | CAN QUARTZ LT-1 | CAN CASTOR OIL, POLYMER WITH TDI NoGS METHYLOXIRANE POLYMER WITH OXIRANE MONOBUTYL ESTER LT-UNK METHYLCHLOROISOTHIAZOLINONE (CIT, CMIT) LT-P1 | MUL PROPYLENE GLYCOL BM-2 | END POLYACRYLIC ACID, SODIUM SALT LT-UNK ALCOHOLS, C9-11, ETHOXYLATED LT-P1 | MUL POLYSILOXANE NoGS 1-PHENOXY-2-PROPANOL LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 1

Contents highest concern GreenScreen Benchmark or List translator Score ... BM-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 20.799 Regulatory (g/l): 48.988
Does the product contain exempt VOCs: No
Are ultra-low VOC tints available: Yes

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: N/A
VOC content: Calculated

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

- Yes
 No

PREPARER: Self-Prepared

VERIFIER:
VERIFICATION #:

SCREENING DATE: 2020-01-06

PUBLISHED DATE: 2020-01-06

EXPIRY DATE: 2023-01-06



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

1240 ACRYSHIELD EXTERIOR FLAT PAINT

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: All raw materials were considered prior to formulation.

OTHER PRODUCT NOTES:

WATER

ID: 558440-22-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2020-01-06

%: 51.25 - 58.64

GS: BM-4

RC: None

NANO: No

ROLE: VEHICLE

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

POLYMETHYL METHACRYLATE (PMMA)

ID: 9011-14-7

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2020-01-06

%: 13.41 - 15.67

GS: LT-P1

RC: None

NANO: No

ROLE: BINDER

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

RESPIRATORY

AOEC - Asthmagens

Asthmagen (Rs) - sensitizer-induced

SUBSTANCE NOTES:

NEPHELINE SYENITE

ID: 37244-96-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2020-01-06

%: 7.55 - 13.84

GS: LT-UNK

RC: None

NANO: No

ROLE: FILLER

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

DIATOMACEOUS EARTH [WHICH CONTAINS LESS THAN 0.1% OF CRYSTALLINE SILICA]

ID: 61790-53-2

%: **2.99 - 4.20** GS: **LT-UNK** RC: **None** NANO: **No** ROLE: **FILLER**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

SOLVENT-DEWAXED HEAVY PARAFFINIC PETROLEUM DISTILLATESID: **64742-65-0**

%: **1.12 - 1.20** GS: **LT-1** RC: **None** NANO: **No** ROLE: **DEFOAMER**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	EU - GHS (H-Statements)	H350 - May cause cancer
CANCER	EU - REACH Annex XVII CMRs	Carcinogen Category 2 - Substances which should be regarded as if they are Carcinogenic to man
MULTIPLE	ChemSec - SIN List	CMR - Carcinogen, Mutagen &/or Reproductive Toxicant
CANCER	EU - Annex VI CMRs	Carcinogen Category 1B - Presumed Carcinogen based on animal evidence
CANCER	GHS - Australia	H350 - May cause cancer

SUBSTANCE NOTES:

1,3-PENTANEDIOL, 2,2,4-TRIMETHYL-, MONOISOBUTYRATEID: **25265-77-4**

%: **0.80 - 2.20** GS: **LT-UNK** RC: **None** NANO: **No** ROLE: **COALESCENT**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	MAK	Carcinogen Group 3A - Evidence of carcinogenic effects but not sufficient to establish MAK/BAT value

SUBSTANCE NOTES:

3(2H)-ISOTHIAZOLONE, 4,5-DICHLORO-2-OCTYL-ID: **64359-81-5**

%: **0.58 - 0.60** GS: **BM-2** RC: **None** NANO: **No** ROLE: **ANTIMICROBIAL**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
ENDOCRINE	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 3 - Severe Hazard to Waters

SUBSTANCE NOTES:

2,2'-ETHYLENEDIOXYDIETHYL BIS(2-ETHYLHEXANOATE)

ID: 94-28-0

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2020-01-06**

%: 0.25 - 0.42	GS: LT-UNK	RC: None	NANO: No	ROLE: COALESCENT
-----------------------	-------------------	-----------------	-----------------	-------------------------

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

AMMONIA

ID: 7664-41-7

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2020-01-06**

%: 0.20 - 0.64	GS: LT-P1	RC: None	NANO: No	ROLE: PRESERVATIVE
-----------------------	------------------	-----------------	-----------------	---------------------------

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
RESPIRATORY	AOEC - Asthmagens	Asthmagen (Rr) - irritant-induced
ACUTE AQUATIC	EU - GHS (H-Statements)	H400 - Very toxic to aquatic life
SKIN IRRITATION	EU - GHS (H-Statements)	H314 - Causes severe skin burns and eye damage
MAMMALIAN	EU - GHS (H-Statements)	H331 - Toxic if inhaled
ENDOCRINE	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
MAMMALIAN	US EPA - EPCRA Extremely Hazardous Substances	Extremely Hazardous Substances

SUBSTANCE NOTES:

1,2-BENZISOTHIAZOLIN-3-ONE (BIT)

ID: 2634-33-5

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2020-01-06**

%: 0.17 - 0.21	GS: LT-P1	RC: None	NANO: No	ROLE: BIOCIDE
-----------------------	------------------	-----------------	-----------------	----------------------

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
ACUTE AQUATIC	EU - GHS (H-Statements)	H400 - Very toxic to aquatic life
SKIN IRRITATION	EU - GHS (H-Statements)	H315 - Causes skin irritation
SKIN SENSITIZE	EU - GHS (H-Statements)	H317 - May cause an allergic skin reaction
EYE IRRITATION	EU - GHS (H-Statements)	H318 - Causes serious eye damage
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
SKIN SENSITIZE	MAK	Sensitizing Substance Sh - Danger of skin sensitization

SUBSTANCE NOTES:

POLOXANLENE

ID: 9003-11-6

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.12 - 0.25**

GS: **LT-UNK**

RC: **None**

NANO: **No**

ROLE: **SURFACTANT**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

HYDROXYETHYL CELLULOSE

ID: **9004-62-0**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.11 - 0.36**

GS: **LT-P1**

RC: **None**

NANO: **No**

ROLE: **RHEOLOGY MODIFIER**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

ENDOCRINE

TEDX - Potential Endocrine Disruptors

Potential Endocrine Disruptor

SUBSTANCE NOTES:

HECTORITE

ID: **12173-47-6**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.10 - 0.20**

GS: **LT-UNK**

RC: **None**

NANO: **No**

ROLE: **RHEOLOGY MODIFIER**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

POLY(OXY-1,2-ETHANEDIYL), ALPHA-TRIDECYL-OMEGA-HYDROXY-, PHOSPHATE, POTASSIUM SALT

ID: **68186-36-7**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.10 - 0.25**

GS: **LT-UNK**

RC: **None**

NANO: **No**

ROLE: **DISPERSANT**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

POLYETHYLENE GLYCOL

ID: **25322-68-3**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.05 - 0.05**

GS: **LT-UNK**

RC: **None**

NANO: **No**

ROLE: **ANTIMICROBIAL**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

SUBSTANCE NOTES:

2-PROPENOIC ACID, POLYMER WITH ETHENYL BENZENE

ID: 25085-34-1

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.00 - 4.06**

GS: **LT-UNK**

RC: **None**

NANO: **No**

ROLE: **BINDER**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

TITANIUM DIOXIDE

ID: 13463-67-7

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.00 - 10.14**

GS: **LT-1**

RC: **None**

NANO: **No**

ROLE: **PIGMENT**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

CANCER

US CDC - Occupational Carcinogens

Occupational Carcinogen

CANCER

CA EPA - Prop 65

Carcinogen - specific to chemical form or exposure route

CANCER

IARC

Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources

ENDOCRINE

TEDX - Potential Endocrine Disruptors

Potential Endocrine Disruptor

CANCER

MAK

Carcinogen Group 3A - Evidence of carcinogenic effects but not sufficient to establish MAK/BAT value

CANCER

MAK

Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels

SUBSTANCE NOTES:

TALC

ID: 14807-96-6

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.00 - 1.24**

GS: **BM-1**

RC: **None**

NANO: **No**

ROLE: **FILLER**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

CANCER

IARC

Group 2b - Possibly carcinogenic to humans

CANCER

MAK

Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification

SUBSTANCE NOTES:

QUARTZ

ID: 14808-60-7

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.00 - 0.13**

GS: **LT-1**

RC: **None**

NANO: **No**

ROLE: **RHEOLOGY MODIFIER**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	IARC	Group 1 - Agent is Carcinogenic to humans
CANCER	US CDC - Occupational Carcinogens	Occupational Carcinogen
CANCER	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CANCER	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CANCER	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CANCER	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CANCER	GHS - New Zealand	6.7A - Known or presumed human carcinogens
CANCER	GHS - Australia	H350i - May cause cancer by inhalation
CANCER	GHS - Japan	Carcinogenicity - Category 1A [H350]

SUBSTANCE NOTES:

CASTOR OIL, POLYMER WITH TDI

ID: 67700-43-0

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.00 - 2.08**

GS: **NoGS**

RC: **None**

NANO: **No**

ROLE: **RHEOLOGY MODIFIER**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

METHYLOXIRANE POLYMER WITH OXIRANE MONOBUTYL ESTER

ID: 9038-95-3

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.00 - 3.10**

GS: **LT-UNK**

RC: **None**

NANO: **No**

ROLE: **RHEOLOGY MODIFIER**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

METHYLCHLOROISOTHIAZOLINONE (CIT, CMIT)

ID: 26172-55-4

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2020-01-06**

%: **0.00 - 0.15**

GS: **LT-P1**

RC: **None**

NANO: **No**

ROLE: **BIOCIDES**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 3 - Severe Hazard to Waters

SUBSTANCE NOTES:

PROPYLENE GLYCOL

ID: 57-55-6

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2020-01-06**%: **0.00 - 0.50**GS: **BM-2**RC: **None**NANO: **No**ROLE: **IN CAN PRESERVATIVE**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

ENDOCRINE**TEDX - Potential Endocrine Disruptors****Potential Endocrine Disruptor**

SUBSTANCE NOTES:

POLYACRYLIC ACID, SODIUM SALT

ID: 9003-04-7

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2020-01-06**%: **0.00 - 1.64**GS: **LT-UNK**RC: **None**NANO: **No**ROLE: **DISPERSANT**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found**No warnings found on HPD Priority Hazard Lists**

SUBSTANCE NOTES:

ALCOHOLS, C9-11, ETHOXYLATED

ID: 68439-46-3

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2020-01-06**%: **0.00 - 0.13**GS: **LT-P1**RC: **None**NANO: **No**ROLE: **WETTING AGENT**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

MULTIPLE**German FEA - Substances Hazardous to Waters****Class 2 - Hazard to Waters**

SUBSTANCE NOTES:

POLYSILOXANE

ID: 9011-19-2

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2020-01-06**%: **0.00 - 0.75**GS: **NoGS**RC: **None**NANO: **No**ROLE: **DISPERSANT**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found**No warnings found on HPD Priority Hazard Lists**

SUBSTANCE NOTES:

1-PHENOXY-2-PROPANOL

ID: 770-35-4

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2020-01-06**%: **0.00 - 0.70**GS: **LT-UNK**RC: **None**NANO: **No**ROLE: **COALESCENT**

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

N/A

CERTIFYING PARTY: Self-declared

ISSUE DATE: 2019-08-

EXPIRY DATE:

CERTIFIER OR LAB: N/A

APPLICABLE FACILITIES: N/A

21

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: No emissions scenario for exterior products.

VOC CONTENT

Calculated

CERTIFYING PARTY: Self-declared

ISSUE DATE: 2018-11-

EXPIRY DATE:

CERTIFIER OR LAB: Kelly-Moore Paint

APPLICABLE FACILITIES: Kelly Moore Paint Hurst Factory

07

Co

301 W Hurst Blvd, Hurst, TX 76053

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: VOC Content value was based on the calculations using internal formulation software.

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

255 ACRYSHIELD WOOD PRIMER

HPD URL: [https://hpdrepository.hpd-](https://hpdrepository.hpd-collaborative.org/repository/HPDs/2861-20150125202226.pdf)

[collaborative.org/repository/HPDs/2861-20150125202226.pdf](https://hpdrepository.hpd-collaborative.org/repository/HPDs/2861-20150125202226.pdf)

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

255 AcryShield Wood Primer is recommended for wood substrate. SURFACE PREPARATION: General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.* New Surfaces: All surfaces should be sound, free of contamination and dry. Wood surfaces should be sanded free of wood fibers. Wood should have a moisture content of less than 15% as measured by a moisture meter. Masonry and plaster should be thoroughly cured before priming. Masonry should have a moisture content of less than 12% as measured by a moisture meter. New Ferrous Metal: Follow general surface preparation guidelines. Remove all loose rust, mill scale, or deteriorated previously applied coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3). New Aluminum Galvanized Metal: Wash thoroughly with TSP or other suitable cleaner/degreaser to remove oil and other contaminants. Rinse thoroughly. Previously Painted Surfaces: Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Sand glossy finishes.*

247

HPD URL: [https://hpdrepository.hpd-](https://hpdrepository.hpd-collaborative.org/repository/HPDs/publish_220_247AcryShield_Exterior_100_Acrylic_Masonry_Primer_1482436329.pdf)

[collaborative.org/repository/HPDs/publish_220_247AcryShield_Exterior_100_Acrylic_Masonry_Primer_1482436329.pdf](https://hpdrepository.hpd-collaborative.org/repository/HPDs/publish_220_247AcryShield_Exterior_100_Acrylic_Masonry_Primer_1482436329.pdf)

MASONRY

PRIMER

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

247 AcryShield Masonry Primer is recommended for Masonry, Stucco & Fiber Cement Board. **SURFACE PREPARATION:** General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.* **New Surfaces:** All surfaces should be sound, free of contamination and dry. Wood surfaces should be sanded free of wood fibers. Wood should have a moisture content of less than 15% as measured by a moisture meter. Masonry and plaster should be thoroughly cured before priming. Masonry should have a moisture content of less than 12% as measured by a moisture meter. **New Ferrous Metal:** Follow general surface preparation guidelines. Remove all loose rust, mill scale, or deteriorated previously applied coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3). **New Aluminum Galvanized Metal:** Wash thoroughly with TSP or other suitable cleaner/degreaser to remove oil and other contaminants. Rinse thoroughly. **Previously Painted Surfaces:** Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Sand glossy finishes.*

5725 DTM PRIMER/FINISH

HPD URL: https://hpdrepository.hpd-collaborative.org/repository/HPDs/publish_220_5725_DTM_Acrylic_Primer_Finisher_1536340863.pdf

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

5725 DTM Primer/Finish is recommended for Metal. **SURFACE PREPARATION:** General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.* **New Surfaces:** All surfaces should be sound, free of contamination and dry. Wood surfaces should be sanded free of wood fibers. Wood should have a moisture content of less than 15% as measured by a moisture meter. Masonry and plaster should be thoroughly cured before priming. Masonry should have a moisture content of less than 12% as measured by a moisture meter. **New Ferrous Metal:** Follow general surface preparation guidelines. Remove all loose rust, mill scale, or deteriorated previously applied coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3). **New Aluminum Galvanized Metal:** Wash thoroughly with TSP or other suitable cleaner/degreaser to remove oil and other contaminants. Rinse thoroughly. **Previously Painted Surfaces:** Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Sand glossy finishes.*

521 PRIME & FILL BLOCK FILLER

HPD URL: **No HPD Available**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

521 Prime & Fill Block Filler is recommended for Porous Masonry. **SURFACE PREPARATION:** General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.* **New Surfaces:** All surfaces should be sound, free of contamination and dry. Wood surfaces should be sanded free of wood fibers. Wood should have a moisture content of less than 15% as measured by a moisture meter. Masonry and plaster should be thoroughly cured before priming. Masonry should have a moisture content of less than 12% as measured by a moisture meter. **New Ferrous Metal:** Follow general surface preparation guidelines. Remove all loose rust, mill scale, or deteriorated previously applied coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3). **New Aluminum Galvanized Metal:** Wash thoroughly with TSP or other suitable cleaner/degreaser to remove oil and other contaminants. Rinse thoroughly. **Previously Painted Surfaces:** Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Sand glossy finishes.*

295 KEL-BOND UNIVERSAL PRIMER

HPD URL: https://hpdrepository.hpd-collaborative.org/repository/HPDs/publish_220_295_Kel_Bond_Universal_Interior_Exterior_Primer_1535046486.pdf

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

295 Kel-Bond Universal Primer is recommended for Stain Blocking. **SURFACE PREPARATION:** General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.* **New Surfaces:** All surfaces should be sound, free of contamination and dry. Wood surfaces should be sanded free of wood fibers. Wood should have a moisture content of less than 15% as measured by a moisture meter. Masonry and plaster should be thoroughly cured before priming. Masonry should have a moisture content of less than 12% as measured by a moisture meter. **New Ferrous Metal:** Follow general surface preparation guidelines. Remove all loose rust, mill scale, or deteriorated previously applied coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3). **New Aluminum Galvanized Metal:** Wash thoroughly with TSP or other suitable cleaner/degreaser to remove oil and other contaminants. Rinse thoroughly. **Previously Painted Surfaces:** Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Sand glossy finishes.*

265 HYBRID PRIMER

HPD URL: **No HPD Available**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

265 Hybrid Primer is recommended for Tannin Rich Wood. SURFACE PREPARATION: General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.* New Surfaces: All surfaces should be sound, free of contamination and dry. Wood surfaces should be sanded free of wood fibers. Wood should have a moisture content of less than 15% as measured by a moisture meter. Masonry and plaster should be thoroughly cured before priming. Masonry should have a moisture content of less than 12% as measured by a moisture meter. New Ferrous Metal: Follow general surface preparation guidelines. Remove all loose rust, mill scale, or deteriorated previously applied coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3). New Aluminum Galvanized Metal: Wash thoroughly with TSP or other suitable cleaner/degreaser to remove oil and other contaminants. Rinse thoroughly. Previously Painted Surfaces: Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Sand glossy finishes.*

287 KEL-BOND ADHESION PLUS

HPD URL: **No HPD Available**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

287 Kel-Bond Adhesion Plus is the recommended primer for Dense or Glossy Surfaces. SURFACE PREPARATION: General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.* New Surfaces: All surfaces should be sound, free of contamination and dry. Wood surfaces should be sanded free of wood fibers. Wood should have a moisture content of less than 15% as measured by a moisture meter. Masonry and plaster should be thoroughly cured before priming. Masonry should have a moisture content of less than 12% as measured by a moisture meter. New Ferrous Metal: Follow general surface preparation guidelines. Remove all loose rust, mill scale, or deteriorated previously applied coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3). New Aluminum Galvanized Metal: Wash thoroughly with TSP or other suitable cleaner/degreaser to remove oil and other contaminants. Rinse thoroughly. Previously Painted Surfaces: Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Sand glossy finishes.*

98 MULTI-SEAL

HPD URL: **No HPD Available**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

98 Multi-Seal is recommended for Chalky Surfaces. SURFACE PREPARATION: General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.* New Surfaces: All surfaces should be sound, free of contamination and dry. Wood surfaces should be sanded free of wood fibers. Wood should have a moisture content of less than 15% as measured by a moisture meter. Masonry and plaster should be thoroughly cured before priming. Masonry should have a moisture content of less than 12% as measured by a moisture meter. New Ferrous Metal: Follow general surface preparation guidelines. Remove all loose rust, mill scale, or deteriorated previously applied coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3). New Aluminum Galvanized Metal: Wash thoroughly with TSP or other suitable cleaner/degreaser to remove oil and other contaminants. Rinse thoroughly. Previously Painted Surfaces: Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Sand glossy finishes.*

Section 5: General Notes

Tintable bases differ primarily in the amount of titanium dioxide included in each formula: light base includes the highest amount of TiO₂ while the neutral base has no TiO₂. Some bases also differ in dispersants, extenders, and thickeners. This product is self-priming over bare wood and masonry <13 pH. A minimum of 2 coats at 4-6 wet mils are required for touch-up, as well as sheen and color uniformity. A minimum of 4 hours are required between applied coats. Over previously painted surfaces, 1-2 coats applied at 4-6 wet mils may be acceptable. An appropriate primer or sealer is required when a porous substrate, heavy tannins, or stains are present.



Section 6: References

MANUFACTURER INFORMATION

MANUFACTURER: **Kelly-Moore Paints**
 ADDRESS: **987 Commercial St**
San Carlos California 94070, USA
 WEBSITE: **www.kellymoore.com**

CONTACT NAME: **Tiffany Gonda**
 TITLE: **Director, Product Stewardship**
 PHONE: **(650) 592-8337**
 EMAIL: **talvarez@kellymoore.com**

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity	GLO Global warming	PHY Physical Hazard (reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive toxicity
DEV Developmental toxicity	MUL Multiple hazards	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	OZO Ozone depletion	LAN Land Toxicity
GEN Gene mutation	PBT Persistent Bioaccumulative Toxic	NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible Benchmark 1
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator Likely Benchmark 1
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS Unknown (no data on List Translator Lists)
BM-U Benchmark Unspecified (insufficient data to benchmark)	

Recycled Types

PreC Preconsumer (Post-Industrial)
PostC Postconsumer
Both Both Preconsumer and Postconsumer
Unk Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.