

CLASSIFICATION: 07 72 33 Thermal and Moisture Protection: Roof Hatches

PRODUCT DESCRIPTION: Roof Hatches provide safe and convenient access to commercial building roof areas using interior ladders and stairs. Nystrom's complete line of Roof Hatch and Safety products meet building codes, fire and life safety requirements. The ThermalMAX Roof Hatch sets the new standard for thermally efficient roof hatches. Designed with a thermal break to keep cool-cool and hot-hot, this hatch boasts an R-20 insulation rating making it today's most energy efficient hatch. Condensation typically occurs on inside surfaces or roof hatches whenever the exterior surface temperature falls below the dew point temperature of the interior space. The thermal break provides a barrier between heat and cold reducing the potential for condensation. This HPD covers Nystrom's ThermalMAX Roof Hatch (RHTA).

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
 Basic Method

Threshold Disclosed Per

- Material
 Product

Threshold level

- 100 ppm
 1,000 ppm
 Per GHS SDS
 Per OSHA MSDS
 Other

Residuals/Impurities

- Considered
 Partially Considered
 Not Considered

Explanation(s) provided
for Residuals/Impurities?

- Yes No

All Substances Above the Threshold Indicated Are:

Characterized Yes Ex/SC Yes No
% weight and role provided for all substances.

Screened Yes Ex/SC Yes No
All substances screened using Priority Hazard Lists with results disclosed.

Identified Yes Ex/SC Yes No
All substances disclosed by Name (Specific or Generic) and Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE

THERMALLY BROKEN ROOF HATCH [6061 ALUMINUM LT-P1 | RES | PHY
| END STEEL NoGS POLYISOCYANURATE FOAM LT-UNK
ETHYLENE/PROPYLENE/DIENE TERPOLYMER (EPDM) LT-UNK
CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE LT-UNK
CELLULOSE PULP NoGS LIMESTONE, CALCIUM CARBONATE LT-UNK
BUTYL RUBBER LT-UNK KAOLIN CLAY LT-UNK | CAN CARBON BLACK
LT-1 | CAN POLYVINYL CHLORIDE (PVC) LT-P1 | RES ANOX 20 LT-UNK
DISTILLATES (PETROLEUM), SOLVENT-REFINED (MILD) HEAVY
PARAFFINIC (9CI) LT-1 | CAN | MUL ZINC LT-P1 | AQU | PHY | END | MUL
PENTANE LT-P1 | AQU | PHY | MAM | MUL]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen
Benchmark or List translator Score ... LT-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.1.1, and discloses hazards associated with all substances present at or above 1000 parts per million (ppm) in the finished product, along with the role and percent weight.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method – Not tested

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

- Yes
 No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2019-07-10

PUBLISHED DATE: 2019-08-15

EXPIRY DATE: 2022-07-10



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

THERMALLY BROKEN ROOF HATCH

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities were considered by following the suggestions of Emerging Best Practices. More than 85% of this product consists of metal alloys, for which Pharos CML may consider the various alloying elements as "Known or Potential Residuals". Therefore, these components have been included in the Substance Notes instead of as individual content entries. Components are listed by name, CASRN, percent by weight (as per supplier SDS), and relevant GreenScreen score.

OTHER PRODUCT NOTES: Percent by weight of substances given as ranges to account for variations in product manufacturing, and due to disclosure preference of suppliers.

6061 ALUMINUM

ID: 7429-90-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-07-10

#: 80.00 - 82.00 GS: LT-P1 RC: Both NANO: No ROLE: Base Metal

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
RESPIRATORY	AOEC - Asthmagens	Asthmagen (Rs) - sensitizer-induced
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Statements)	H228 - Flammable solid
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Statements)	H250 - Catches fire spontaneously if exposed to air
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Statements)	H261 - In contact with water releases flammable gases
ENDOCRINE	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor

SUBSTANCE NOTES: Recycled content confirmed by supplier to range from 5% to 60%, with 35% average recycled content. Documentation from supplier provides the following composition for alloying elements that may individually exceed the declared threshold: Max 2.8% Zinc [7440-66-6; LT-P1]; Max 2.0% Manganese [7439-96-5; LT-P1]; Max 1.9% Silicon [7440-21-3; LT-UNK]; Max 1.6% Magnesium [7439-95-4; LT-UNK]; Max 1.1% Iron [7439-89-6; LT-P1]; Max 0.5% Chromium [7440-47-3; LT-P1]. Specific guidelines are being created to address known issues related to transparency and disclosure for several materials ("Special Conditions"), including those with Form-Specific Hazards such as Aluminum.

STEEL

ID: 12597-69-2

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-07-10

#: 6.50 - 6.60 GS: NoGS RC: UNK NANO: No ROLE: Base Metal

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
-------------	------------------------	----------

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Various mixed hardware/fasteners. Documentation from supplier provides the following composition for alloying elements that may individually exceed the declared threshold: max 3.1% Silicon [7440-21-3; LT-UNK]; max 2.5% Manganese [7439-96-5; LT-P1]; max 1.6% Aluminum [7429-90-5; LT-P1]; max 1.8% Nickel [7440-02-0; LT-1]; max 1.0% Chromium [7440-47-3; LT-P1]; max 0.2% Vanadium [7440-62-2; LT-1].

POLYISOCYANURATE FOAM

ID: 9063-78-9

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2019-07-10**

#: **6.10 - 6.90** GS: **LT-UNK** RC: **None** NANO: **No** ROLE: **Insulation**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
-------------	------------------------	----------

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Foam insulation.

ETHYLENE/PROPYLENE/DIENE TERPOLYMER (EPDM)

ID: 25038-36-2

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2019-07-10**

#: **3.20 - 3.40** GS: **LT-UNK** RC: **None** NANO: **No** ROLE: **Base Polymer**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
-------------	------------------------	----------

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Rubber curb; rubber washer; gasket.

CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE

ID: 65997-17-3

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2019-07-10**

#: **0.10 - 1.60** GS: **LT-UNK** RC: **None** NANO: **No** ROLE: **Reinforcement**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
-------------	------------------------	----------

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Foam insulation.

CELLULOSE PULP

ID: 65996-61-4

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2019-07-10**

#: **0.10 - 1.60** GS: **NoGS** RC: **None** NANO: **No** ROLE: **Reinforcement**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists
SUBSTANCE NOTES: Foam insulation. Identified on the US EPA Safer Chemical Ingredient List (Green Circle - Verified Low Concern).		

LIMESTONE, CALCIUM CARBONATE

ID: 1317-65-3

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-07-10		
%: 0.10 - 1.00	GS: LT-UNK	RC: None	NANO: No	ROLE: Filler, Extender
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: Sealant tape; red vinyl grip handle. Identified on the US EPA Safer Chemical Ingredient List (Green Circle - Verified Low Concern).				

BUTYL RUBBER

ID: 9010-85-9

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-07-10		
%: 0.10 - 0.30	GS: LT-UNK	RC: None	NANO: No	ROLE: Base Polymer
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: Sealant tape; gasket.				

KAOLIN CLAY

ID: 1332-58-7

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-07-10		
%: 0.10 - 0.30	GS: LT-UNK	RC: None	NANO: No	ROLE: Filler, Extender
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
CANCER	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
SUBSTANCE NOTES: Sealant tape; gasket.				

CARBON BLACK

ID: 1333-86-4

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-07-10		
%: 0.10 - 0.40	GS: LT-1	RC: None	NANO: No	ROLE: Pigment

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	US CDC - Occupational Carcinogens	Occupational Carcinogen
CANCER	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CANCER	IARC	Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources
CANCER	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification

SUBSTANCE NOTES: Rubber curb; rubber washer; gasket; sealant tape. Carbon black is one of several compounds with warnings restricted to unbound/respirable forms.

POLYVINYL CHLORIDE (PVC)

ID: 9002-86-2

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-07-10**

#: **0.05 - 0.10**

GS: **LT-P1**

RC: **None**

NANO: **No**

ROLE: **Base Polymer**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
RESPIRATORY	AOEC - Asthmagens	Asthmagen (Rs) - sensitizer-induced

SUBSTANCE NOTES: Red vinyl grip handle.

ANOX 20

ID: 6683-19-8

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-07-10**

#: **0.05 - 0.20**

GS: **LT-UNK**

RC: **None**

NANO: **No**

ROLE: **Antioxidant**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Sealant tape. Identified on the US EPA Safer Chemical Ingredient List (Green Circle - Verified Low Concern).

DISTILLATES (PETROLEUM), SOLVENT-REFINED (MILD) HEAVY PARAFFINIC (9CI)

ID: 64741-88-4

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-07-10**

#: **0.01 - 0.10**

GS: **LT-1**

RC: **None**

NANO: **No**

ROLE: **Raw Material**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	EU - GHS (H-Statements)	H350 - May cause cancer
CANCER	EU - REACH Annex XVII CMRs	Carcinogen Category 2 - Substances which should be regarded as if they are Carcinogenic to man
MULTIPLE	ChemSec - SIN List	CMR - Carcinogen, Mutagen &/or Reproductive Toxicant
CANCER	EU - Annex VI CMRs	Carcinogen Category 1B - Presumed Carcinogen based on animal evidence
CANCER	Australia - GHS	H350 - May cause cancer

SUBSTANCE NOTES: Sealant tape; gasket.

ZINC ID: 7440-66-6

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-07-10**

#: **0.01 - 0.10**

GS: **LT-P1**

RC: **None**

NANO: **No**

ROLE: **Metallic Coating**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
ACUTE AQUATIC	EU - GHS (H-Statements)	H400 - Very toxic to aquatic life
CHRON AQUATIC	EU - GHS (H-Statements)	H410 - Very toxic to aquatic life with long lasting effects
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Statements)	H250 - Catches fire spontaneously if exposed to air
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Statements)	H260 - In contact with water releases flammable gases which may ignite spontaneously
ENDOCRINE	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters

SUBSTANCE NOTES: Zinc plated steel for various hardware/fasteners. Specific guidelines are being created to address known issues related to transparency and disclosure for several materials ("Special Conditions"), including those with Form-Specific Hazards such as Zinc.

PENTANE ID: 109-66-0

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-07-10**

#: **Impurity/Residual**

GS: **LT-P1**

RC: **None**

NANO: **No**

ROLE: **Impurity/Residual**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CHRON AQUATIC	EU - GHS (H-Statements)	H411 - Toxic to aquatic life with long lasting effects
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Statements)	H225 - Highly flammable liquid and vapour
MAMMALIAN	EU - GHS (H-Statements)	H304 - May be fatal if swallowed and enters airways
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters

SUBSTANCE NOTES: **Blowing agent for foam insulation.**

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

CDPH Standard Method – Not tested

CERTIFYING PARTY: **Self-declared**

ISSUE DATE: **2019-**

EXPIRY DATE:

CERTIFIER OR LAB: **N/A**

APPLICABLE FACILITIES: **N/A**

05-20

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES:

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

SAFETY RAILING

HPD URL: <https://www.nystrom.com/products/fall-protection/roof-hatch-safety-railing>

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

OSHA compliant fall protection safety railings and posts specifically designed for Roof Hatches, Smoke Vents and Floor Doors.

Section 5: General Notes



MANUFACTURER INFORMATION

MANUFACTURER: **Nystrom**
ADDRESS: **9300 73rd Avenue North**
Minneapolis MN 55428, USA
WEBSITE: **www.nystrom.com**

CONTACT NAME: **Sandy McWilliams**
TITLE: **Director of Business Development**
PHONE: **(800) 547-2635**
EMAIL: **SMcWilliams@nystrom.com**

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity	GLO Global warming	PHY Physical Hazard (reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive toxicity
DEV Developmental toxicity	MUL Multiple hazards	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	OZO Ozone depletion	LAN Land Toxicity
GEN Gene mutation	PBT Persistent Bioaccumulative Toxic	NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible Benchmark 1
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator Likely Benchmark 1
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS Unknown (no data on List Translator Lists)
BM-U Benchmark Unspecified (insufficient data to benchmark)	

Recycled Types

PreC Preconsumer (Post-Industrial)
PostC Postconsumer
Both Both Preconsumer and Postconsumer
Unk Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.