PABCO® ABUSE CURB® Type X Gypsum Panel by PABCO Gypsum

Health Product Declaration v2.1.1

created via: HPDC Online Builder

CLASSIFICATION: 09 29 00 Finishes: Gypsum Board

PRODUCT DESCRIPTION: PABCO® ABUSE CURB® Type X gypsum panels are designed for interior wall assemblies where enhanced resistance to abrasion, indentation, mold, and moisture is crucial. The proprietary high-density and fireresistant Type X gypsum core is formulated with the MOLD CURB® Plus technology and encased in heavy and durable 100% recycled moisture, mold, mildew, and abrasion-resistant paper.



Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
- Basic Method

Threshold Disclosed Per

- Material
- Product

Threshold level

- C 100 ppm
- € 1,000 ppm
- Per GHS SDS
- C Per OSHA MSDS
- C Other

Residuals/Impurities

- Considered
- C Partially Considered
- Not Considered

Explanation(s) provided for Residuals/Impurities? Yes No

All Substances Above the Threshold Indicated Are:

Characterized

% weight and role provided for all substances.

Screened

○ Yes Ex/SC Yes No

All substances screened using Priority Hazard Lists with results disclosed.

Identified

O Yes Ex/SC O Yes O No

All substances disclosed by Name (Specific or Generic) and Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

PABCO® ABUSE CURB® TYPE X GYPSUM PANEL [CALCIUM SULFATE DIHYDRATE LT-UNK CELLULOSE PULP NoGS PARAFFIN LT-UNK STARCH LT-UNK CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE LT-UNK DEXTRIN LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 0 Contents highest concern GreenScreen Benchmark or List translator Score ... LT-UNK Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method V1.2 (Section 01350/CHPS) -Classroom & Office scenario

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

C Yes No

PREPARER: Self-Prepared VFRIFIFR:

VERIFICATION #:

SCREENING DATE: 2019-01-02 PUBLISHED DATE: 2019-01-07 EXPIRY DATE: 2022-01-02



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-standard

PABCO® ABUSE CURB® TYPE X GYPSUM PANEL

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Raw material obtained from naturally occurring gypsum mineral may contain crystalline silica. The amount of silica that can be reduced to respirable is dependent on many factors and testing has shown that the cut and score method does not produce respirable silica above OSHA Permissible Exposure Limit (PEL).

OTHER PRODUCT NOTES:

CALCIUM SULFATE DIHYDRATE				ID: 10101-41-4
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-01-02		
%: 85.0000 - 95.0000	GS: LT-UNK	RC: PreC	nano: No	ROLE: Core Substrate
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
	No hazards found			
SUBSTANCE NOTES:				

CELLULOSE PULP				ID: 65996-61- 4
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-01-02		
%: 4.0000 - 10.0000	gs: NoGS	RC: Both	nano: No	ROLE: Core Encasing
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
	No hazards found			
SUBSTANCE NOTES: 100% Re	cycled Paper Facings			

PARAFFIN				ID: 8002-74-2
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-01-02		
%: 3.0000 - 5.0000	GS: LT-UNK	RC: UNK	nano: No	ROLE: Water Repellent
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS	3	

SUBSTANCE NOTES:

STARCH				ID: 9005-25-8
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-01-02		
%: 0.1000 - 0.5000	GS: LT-UNK	RC: UNK	nano: No	ROLE: Core Adhesive
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
	No hazards found			

CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE

ID: **65997-17-3**

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-01-02		
%: 0.1000 - 0.3000	GS: LT-UNK	RC: UNK	NANO: No	ROLE: Core Strengthing
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
	No hazards found			

SUBSTANCE NOTES:

SUBSTANCE NOTES:

DEXTRIN				ID: 9004-53- 9
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-01-02		
%: 0.1000 - 0.2000	GS: LT-UNK	RC: UNK	nano: No	ROLE: Drying Additive

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

No hazards found

SUBSTANCE NOTES:



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom &

Office scenario

10-19

CERTIFYING PARTY: Third Party

APPLICABLE FACILITIES: PABCO® Gypsum 8000 E

Lake Mead Blvd. Las Vegas, NV 89115 United

States

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES:

ISSUE DATE: 2019-EXPIRY DATE:

CERTIFIER OR LAB: Berkeley

Analytical

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

HPD URL: No HPD Available **FRAMING**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Framing material, i.e. wood or steel, shall be selected per building codes, fire design, or acoustical design as specified in the Basis of Design (BOD).

FASTENERS HPD URL: No HPD Available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Fasteners, i.e. nail or screw, shall be selected per building codes, fire design, or acoustical design as specified in the Basis of Design (BOD).

JOINT TAPING HPD URL: No HPD Available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Joint taping shall be used in gypsum board finishing per Level of Finish as specified in the Basis of Design (BOD).

JOINT COMPOUND HPD URL: No HPD Available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Joint compound shall be used in gypsum board finishing per Level of Finish as specified in the Basis of Design (BOD).



Section 5: General Notes

This Health Product Declaration (HPD) was completed in accordance with the discloses hazards associated with all substances present at or above 1000 pa	
product, along with the role and percent weight.	(III)
ABCO ABUSE CURB Type X Gypsum Panel	

MANUFACTURER INFORMATION

MANUFACTURER: PABCO Gypsum

ADDRESS: PO Box 364329

North Las Vegas Nevada 89036, United States

WEBSITE: www.pabcogypsum.com

CONTACT NAME: Deborah Callaway

TITLE: Technical Services Manager--Gypsum

PHONE: **702-956-2413**

EMAIL: deborah.callaway@pabcogypsum.com

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity **END** Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

MAM Mammalian/systemic/organ toxicity

MUL Multiple hazards

NEU Neurotoxicity

OZO Ozone depletion

PBT Persistent Bioaccumulative Toxic

PHY Physical Hazard (reactive)
REP Reproductive toxicity

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

LAN Land Toxicity

NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insuficient data to benchmark)

Recycled Types

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

Both Both Preconsumer and Postconsumer
Unk Inclusion of recycled content is unknown

None Does not include recycled content

LT-P1 List Translator Possible Benchmark 1 LT-1 List Translator Likely Benchmark 1

LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)

NoGS Unknown (no data on List Translator Lists)

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances
 created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.