SpecSeal® Series SSW BLU220, BLU230, BLU240 Intumescent Wrap Strip by Specified Technologies Inc.

Health Product Declaration v2.1.1

created via: HPDC Online Builder

CLASSIFICATION: 07 84 00 Firestopping, 07 84 13 Penetration Firestopping PRODUCT DESCRIPTION: SpecSeal® Wrap Strips are highly flexible, elastomeric strips designed to firestop combustible penetrations in fire-rated floors, floor/ceilings, and walls. Convenient 12' (3.7 m) rolls, or individually sized strips facilitate installation and minimize waste. These products utilize STI's fast responding intumescent technology, providing very responsive and highly directionalized expansion. Rapid expansion provides quick closure for burning combustible penetrants. When exposed to temperatures in excess of 250°F (121°C), the SpecSeal® Wrap Strip begins to expand (intumesce) rapidly to form a dense, highly insulative char. Free expansion varies according to the grade utilized (See Table A). Expansion continues up to temperatures of 1,000°F (538°C).



Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

Nested Materials Method Rasic Method

Threshold Disclosed Per

Material

Product

Threshold level

C 100 ppm

⊙ 1,000 ppm C Per GHS SDS

C Per OSHA MSDS

Other

Residuals/Impurities

Considered

C Partially Considered

C Not Considered

Explanation(s) provided for Residuals/Impurities?

• Yes • No

All Substances Above the Threshold Indicated Are:

Characterized ○ Yes Ex/SC Yes No

% weight and role provided for all substances.

 ○ Yes Ex/SC Yes No Screened

All substances screened using Priority Hazard Lists with results disclosed.

C Yes Ex/SC C Yes € No Identified

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL I SUBSTANCE I RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SPECSEAL® SERIES SSW BLU220, BLU230, BLU240 INTUMESCENT WRAP STRIP [GRAPHITE LT-UNK UNDISCLOSED LT-UNK UNDISCLOSED NoGS METHYLENE BISPHENYL DIISOCYA<u>NATE</u> (PURE MDI) LT-UNK | RES | MUL | SKI | EYE | CAN 2,2'-BIS-6-TERC.BUTYL-P-KRESYLMETHAN LT-P1 | END | REP POLYMERIC MDI (PMDI) LT-UNK | RES | MUL | CAN]

Number of Greenscreen BM-4/BM3 contents ... 0 Contents highest concern GreenScreen Benchmark or List translator Score ... LT-P1 Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: N/A

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

C Yes O No

PREPARER: Self-Prepared VERIFIER: VERIFICATION #:

SCREENING DATE: 2019-03-20 PUBLISHED DATE: 2019-03-21 EXPIRY DATE: 2022-03-20

SpecSeal Series SSW BLU220, BLU230, BLU240 Intumescent Wrap Strip hpdrepository.hpd-collaborative.org



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-standard

SPECSEAL® SERIES SSW BLU220, BLU230, BLU240 INTUMESCENT WRAP STRIP PRODUCT THRESHOLD: 1000 ppm RESIDUALS AND IMPURITIES CONSIDERED: Yes RESIDUALS AND IMPURITIES NOTES: This material does not contain any residuals. OTHER PRODUCT NOTES: This material does not contain any residuals. GRAPHITE ID: 7782-42-5 HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2019-03-20 %: 30.0000 - 60.0000 GS: LT-UNK RC: None NANO: No ROLE: intumescent HAZARD TYPE AGENCY AND LIST TITLES No hazards found SUBSTANCE NOTES: This material is the intumescent in the product. UNDISCLOSED HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2019-03-20 %: 25.0000 - 40.0000 GS: LT-UNK ROLE: binder RC: None NANO: No HAZARD TYPE AGENCY AND LIST TITLES WARNINGS No hazards found SUBSTANCE NOTES: This material is the binder in the product. UNDISCLOSED HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2019-03-20 %: **15.0000 - 30.0000** GS: NoGS RC: None NANO: No ROLE: plasticizer HAZARD TYPE No hazards found SUBSTANCE NOTES: This material is the plasticizer in the product. METHYLENE BISPHENYL DIISOCYANATE (PURE MDI) ID: 101-68-8 HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2019-03-20 %: 2.0000 - 4.0000 GS: LT-UNK RC: None NANO: No ROLE: binder

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
RESPIRATORY	AOEC - Asthmagens	Asthmagen (G) - generally accepted		
RESTRICTED LIST	US EPA - PPT Chemical Action Plans	EPA Chemical of Concern - Action Plan published		
SKIN IRRITATION	EU - GHS (H-Statements)	H315 - Causes skin irritation		
SKIN SENSITIZE	EU - GHS (H-Statements)	H317 - May cause an allergic skin reaction		
EYE IRRITATION	EU - GHS (H-Statements)	H319 - Causes serious eye irritation		
RESPIRATORY	EU - GHS (H-Statements)	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled		
CANCER	EU - GHS (H-Statements)	H351 - Suspected of causing cancer		
RESPIRATORY	US EPA - PPT Chemical Action Plans	Inhalation sensitizer causing asthma and lung damage		
CANCER	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels		
RESPIRATORY	MAK	Sensitizing Substance Sah - Danger of airway & skin sensitization		

 $\mbox{\scriptsize SUBSTANCE}$ NOTES: This material is part of the binder in the product.

2,2'-BIS-6-TERC.BUTYL-P-KRESYLMETHAN

ID: 119-47-1

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-03-20			
%: 0.5000 - 1.5000	GS: LT-P1	RC: None	1	nano: No	ROLE: antioxidant
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS		
ENDOCRINE	TEDX - Potential Endocrine Disruptors		Potential Endocrine Disruptor		
REPRODUCTIVE	Australia - GHS		H360F - May damage fertility		

 $\mbox{\scriptsize SUBSTANCE}$ NOTES: This material is the antioxidant in the product.

POLYMERIC MDI (PMDI) ID: 9016-87-9

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-03-20					
%: 0.2000 - 0.5000	GS: LT-UNK	RC: None	nano: No	ROLE: binder			
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS					
RESPIRATORY	AOEC - Asthmagens	Asthmagen (G) - g	Asthmagen (G) - generally accepted				
RESTRICTED LIST	US EPA - PPT Chemical Action Plans	EPA Chemical of C	EPA Chemical of Concern - Action Plan published				
RESPIRATORY	US EPA - PPT Chemical Action Plans	Inhalation sensitize	Inhalation sensitizer causing asthma and lung damage				
CANCER	MAK	Carcinogen Group levels	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels				
RESPIRATORY	MAK	Sensitizing Substa	Sensitizing Substance Sah - Danger of airway & skin sensitization				

 $\mbox{\scriptsize SUBSTANCE}$ NOTES: This material is part of the binder in the product.



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS N/A

CERTIFYING PARTY: Self-declared ISSUE EXPIRY CERTIFIER APPLICABLE FACILITIES: All. DATE: DATE: OR LAB: 2017-Self-07-12 declared.

https://files.stifirestop.com/5.%20Safety%20Data%20Sheets/1.%20English/SDS_BLU220,%20BLU230,%20BLU240%20Wrap%20Strip.pdf

CERTIFICATION AND COMPLIANCE NOTES: Not applicable. Not a wet applied product or type of insulation. See SDS under Certificate URL.



Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available. No accessories are required for this product.



Section 5: General Notes

Applications SpecSeal® Wrap Strips are used for firestopping combustible penetrants such as nonmetallic pipes or pipe insulation. Installations were developed for both "tuck-in" applications (where strips are secured around the penetrant and slid into the opening) and restraining collar assemblies (for surface mounting). For larger openings or complex penetrant configurations, systems were developed utilizing wrap strips in conjunction with other SpecSeal® products. SpecSeal® Wrap Strips are suitable for use in all common forms of construction including concrete floors, concrete over steel deck, concrete walls, concrete block walls, gypsum board/stud walls, and wood floor/ ceiling assemblies. Specifications The wrap strip material shall be a highly flexible, intumescent material. The wrap strip shall contain no water soluble expansion ingredients and provide a minimum of 20x free expansion. The intumescent wrap strip shall be faced on each side with plastic. The specified material shall be approved for a wide range of applications including combustible and noncombustible penetrants when used by itself or in combination with other products from the same manufacturer. The wrap strip shall be UL Certified and tested to the requirements of ASTM E814 (UL 1479), CAN/ULC S115. Specified Divisions Division 7 07 84 13 Penetration Firestopping Division 22 22 00 00 Plumbing Performance SpecSeal® Wrap Strips are the basis for systems that meet the exacting criteria of ASTM E814 (UL 1479), CAN/ULC S115. Systems were tested for all common forms of construction and penetrants with ratings up to 4 hours (dependent upon grade of wrap strip utilized). Features & Benefits • Rapid Expansion: Closes off burning penetrants faster. • High Volume Char: Significant expansion seals off opening! • Water-Resistant: No soluble or hygroscopic ingredients. • Economical: 12' (3.7 m) rolls or precut strips means no piecing...less waste! • Highly Flexible: No foil...soft...supple...easier to install! • Versatile: Performer for a wide range of complex applications.

MANUFACTURER INFORMATION

MANUFACTURER: Specified Technologies Inc.

ADDRESS: 210 Evans Way

Somerville NJ 08876, United States

WEBSITE: www.stifirestop.com

CONTACT NAME: George Gornick, LEED Green

Associate

TITLE: Applications Engineer PHONE: 800-992-1180, Ext. 1013 EMAIL: ggornick@stifirestop.com

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insuficient data to benchmark)

Recycled Types

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

Both Both Preconsumer and Postconsumer

Unk Inclusion of recycled content is unknown

None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

GLO Global warming PHY Physical Hazard (reactive) MAM Mammalian/systemic/organ toxicity

MUL Multiple hazards **NEU** Neurotoxicity

OZO Ozone depletion

PBT Persistent Bioaccumulative Toxic

REP Reproductive toxicity **RES** Respiratory sensitization SKI Skin sensitization/irritation/corrosivity **LAN** Land Toxicity

NF Not found on Priority Hazard Lists

LT-P1 List Translator Possible Benchmark 1 LT-1 List Translator Likely Benchmark 1

LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark) NoGS Unknown (no data on List Translator Lists)

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard