

CLASSIFICATION: 07-84-00-FireStopping

PRODUCT DESCRIPTION: 3M™ Fire Barrier Sealant IC 15WB+ is a cost-effective, one-part, gun-grade, latex-based, intumescent firestop sealant that dries to form a monolithic firestop seal that also acts as a barrier to airborne sound transmission. 3M™ Fire Barrier Sealant IC 15WB+ firestops through penetrations passing through fire-rated floor, floor/ceiling or wall assemblies, as well as other fire-rated interior building partitions and assemblies (e.g. static construction joints or blank openings)

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
- Basic Method

Threshold Disclosed Per

- Material
- Product

Threshold level

- 100 ppm
- 1,000 ppm
- Per GHS SDS
- Per OSHA MSDS
- Other

Residuals/Impurities

- Considered
- Partially Considered
- Not Considered

Explanation(s) provided for Residuals/Impurities?
 Yes No

All Substances Above the Threshold Indicated Are:

Characterized Yes Ex/SC Yes No
% weight and role provided for all substances.

Screened Yes Ex/SC Yes No
All substances screened using Priority Hazard Lists with results disclosed.

Identified Yes Ex/SC Yes No
One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE

3M FIREBARRIER™ SEALANT IC 15 WB+ [LIMESTONE; CALCIUM CARBONATE LT-UNK WATER BM-4 UNDISCLOSED NoGS ZINC BORATE (FIREBRAKE ZB) NoGS SODIUM SILICATE LT-P1 | END 2-AMINO-2-METHYL-1-PROPANOL LT-UNK | SKI | EYE QUARTZ LT-1 | CAN]

Number of Greenscreen BM-4/BM3 contents ... 1

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-1
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Ingredients above 1000 ppm and meeting US GHS disclosure requirements are disclosed.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 3.96 Regulatory (g/l): 3.96
Does the product contain exempt VOCs: No
Are ultra-low VOC tints available: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method V1.1 (Section 01350/CHPS) - Zero VOC emissions
VOC content: Intertek ISO 17025 Certified Lab

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

- Yes
- No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2018-10-02

PUBLISHED DATE: 2019-01-14

EXPIRY DATE: 2021-10-02



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-standard

3M FIREBARRIER™ SEALANT IC 15 WB+

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Partially

RESIDUALS AND IMPURITIES NOTES: Residual and impurities are considered if >1000 ppm

OTHER PRODUCT NOTES: This is a fire barrier/stop product. A firestop is a passive fire protection system made up of various components and used to seal openings and joints in a fire-resistance-rated wall or floor assembly.

LIMESTONE; CALCIUM CARBONATE

ID: 1317-65-3

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2018-10-02

#: 30.0000 - 60.0000

GS: LT-UNK

RC: None

NANO: No

ROLE: Filler

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

No hazards found

SUBSTANCE NOTES: Limestone, Use as filler

WATER

ID: 7732-18-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2018-10-02

#: 10.0000 - 30.0000

GS: BM-4

RC: None

NANO: No

ROLE: Diluent

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

No hazards found

SUBSTANCE NOTES: water

UNDISCLOSED

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2018-10-02

#: 10.0000 - 30.0000

GS: NoGS

RC: None

NANO: No

ROLE: Binder

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

No hazards found

SUBSTANCE NOTES: This is an acrylate polymer which has no cas number. This is a polymer solid.

ZINC BORATE (FIREBRAKE ZB)

ID: 138265-88-0

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2018-10-02**

?: **3.0000 - 7.0000**

GS: **NoGS**

RC: **None**

NANO: **No**

ROLE: **Flame retardant**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

No hazards found

SUBSTANCE NOTES: zinc borate 2335

SODIUM SILICATE

ID: 1344-09-8

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2018-10-02**

?: **3.0000 - 7.0000**

GS: **LT-P1**

RC: **None**

NANO: **No**

ROLE: **Filler**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

ENDOCRINE

TEDX - Potential Endocrine Disruptors

Potential Endocrine Disruptor

SUBSTANCE NOTES: sodium silicate

2-AMINO-2-METHYL-1-PROPANOL

ID: 124-68-5

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2018-10-02**

?: **0.0000 - 0.5000**

GS: **LT-UNK**

RC: **None**

NANO: **No**

ROLE: **Buffer**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

SKIN IRRITATION

EU - GHS (H-Statements)

H315 - Causes skin irritation

EYE IRRITATION

EU - GHS (H-Statements)

H319 - Causes serious eye irritation

SUBSTANCE NOTES: Buffer solution

QUARTZ

ID: 14808-60-7

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2018-10-02**

?: **0.0000 - 0.5000**

GS: **LT-1**

RC: **None**

NANO: **No**

ROLE: **Filler**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	US CDC - Occupational Carcinogens	Occupational Carcinogen
CANCER	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CANCER	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CANCER	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CANCER	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CANCER	New Zealand - GHS	6.7A - Known or presumed human carcinogens
CANCER	Japan - GHS	Carcinogenicity - Category 1A
CANCER	Australia - GHS	H350i - May cause cancer by inhalation

SUBSTANCE NOTES: **Quartz silica**

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

CDPH Standard Method V1.1 (Section 01350/CHPS) - Zero VOC emissions

CERTIFYING PARTY: **Self-declared** ISSUE DATE: **2016-09-30** EXPIRY DATE: **2020-09-30** CERTIFIER OR LAB: **Intertek Lab**
APPLICABLE FACILITIES: **3M Company Facility**
CERTIFICATE URL:
CERTIFICATION AND COMPLIANCE NOTES: **None**

VOC CONTENT

Intertek ISO 17025 Certified Lab

CERTIFYING PARTY: **Self-declared** ISSUE DATE: **2016-09-30** EXPIRY DATE: **2020-09-30** CERTIFIER OR LAB: **Intertek ISO certified lab**
APPLICABLE FACILITIES: **3M Company Facility**
CERTIFICATE URL:
CERTIFICATION AND COMPLIANCE NOTES:

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

NO ACCESSORIES

HPD URL: **No HPD available**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

3M FireBarrier™ Sealant IC 15 WB+ is typically used in mechanical, electrical and plumbing applications to firestop openings created by metallic pipe, plastic pipe, conduit, power and communication cable etc...

Section 5: General Notes

3M does not agree with all the hazard statements generated by the HPD web-based tool. 3M provides other documentation to help assess health and environmental hazards and risks from this product. Please find a GHS-compliant Safety Data Sheet and a regulatory certificate, which includes information on specific applicable regulations and typical chemicals of concern, at www.3m.com/regs. If further health hazard information is required, please contact 3M customer contact center at 1-800-362-3550. Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information. Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance

of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

MANUFACTURER INFORMATION

MANUFACTURER: **3M Company**

ADDRESS: **3M Center**

Saint Paul MN 55144, USA

WEBSITE: **https://www.3m.com/3M/en_US/company-us/all-3m-products/~/3M-Fire-Barrier-Sealant-IC-15WB-/?N=5002385+3293123898&rt=rud**

CONTACT NAME: **Chee Nguyen**

TITLE: **Regulatory Affairs Specialist**

PHONE: **651-733-8978**

EMAIL: **tmnguyen2@mmm.com**

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

MAM Mammalian/systemic/organ toxicity

MUL Multiple hazards

NEU Neurotoxicity

OZO Ozone depletion

PBT Persistent Bioaccumulative Toxic

PHY Physical Hazard (reactive)

REP Reproductive toxicity

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

LAN Land Toxicity

NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insufficient data to benchmark)

LT-P1 List Translator Possible Benchmark 1

LT-1 List Translator Likely Benchmark 1

LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)

NoGS Unknown (no data on List Translator Lists)

Recycled Types

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

Both Both Preconsumer and Postconsumer

Unk Inclusion of recycled content is unknown

None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material

Nested Method / Product Threshold Substances listed within each material per threshold indicated per product

Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this

