

Uninsulated Fire-Rated Access Doors by Babcock-Davis

Health Product Declaration v2.1.1

created via: HPDC Online Builder

CLASSIFICATION: 08 31 00 Openings: Access Doors and Panels

PRODUCT DESCRIPTION: Babcock-Davis' Uninsulated Fire Rated Access Doors are a cost effective access solution for fire-rated walls. UL Listed "B" label for 1-1/2 hours, these doors do not carry the temperature rise rating. This HPD covers Babcock-Davis' Uninsulated Fire-Rated Access Doors (BUT,BUW,BUP) with standard features. Optional accessories are included in Section 4: Accessories.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
 Basic Method

Threshold Disclosed Per

- Material
 Product

Threshold level

- 100 ppm
 1,000 ppm
 Per GHS SDS
 Per OSHA MSDS
 Other

Residuals/Impurities

- Considered
 Partially Considered
 Not Considered

Explanation(s) provided
for Residuals/Impurities?

- Yes No

All Substances Above the Threshold Indicated Are:

Characterized Yes Ex/SC Yes No

% weight and role provided for all substances.

Screened Yes Ex/SC Yes No

All substances screened using Priority Hazard Lists with results disclosed.

Identified Yes Ex/SC Yes No

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

UNINSULATED FIRE-RATED ACCESS DOORS [STEEL NoGS STAINLESS STEEL NoGS ZINC LT-P1 | AQU | PHY | END | MUL ALUMINA TRIHYDRATE BM-2 | RES TITANIUM DIOXIDE LT-1 | CAN | END UNDISCLOSED NoGS]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.1.1, and discloses hazards associated with all substances present at or above 1000 parts per million (ppm) in the finished product, along with the role and percent weight. Substances not "Identified" are those considered proprietary to suppliers.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: Inherently non-emitting source per LEED®

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

- Yes
 No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2019-07-15

PUBLISHED DATE: 2019-07-30

EXPIRY DATE: 2022-07-15



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

UNINSULATED FIRE-RATED ACCESS DOORS

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities were considered by following the suggestions of Emerging Best Practices. Approximately 99% of this product consists of metal alloys, for which Pharos CML considers the various alloying elements as "Known or Potential Residuals". Thus, these components have been included in the Substance Notes instead of as individual content entries, with components listed by name, CASRN, percent by weight (as per supplier SDS), and relevant GreenScreen score.

OTHER PRODUCT NOTES: Percent by weight of substances given as ranges to account for material differences between product lines.

STEEL

ID: 12597-69-2

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-07-15

%: 97.00 - 99.00

GS: NoGS

RC: Both

NANO: No

ROLE: Base Metal

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Standard door and frame, spring, bracket, hinge, latch, mixed hardware. Alternate door and frame available in stainless steel. Recycled content confirmed by suppliers for steel used in product ranges from 18.5% total (14.0% pre-consumer and 4.5% post-consumer recycled scrap) to 97.8% total (36.5% pre-consumer and 61.3% post-consumer recycled scrap). Documentation from supplier provides the following composition for alloying elements that may individually exceed the declared threshold: max 3.1% Silicon [7440-21-3; LT-UNK]; max 2.5% Manganese [7439-96-5; LT-P1]; max 1.6% Aluminum [7429-90-5; LT-P1]; max 1.8% Nickel [8049-31-8; LT-1]; max 1% Chromium [7440-47-3; LT-P1].

STAINLESS STEEL

ID: 12597-68-1

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-07-15

%: 90.00 - 92.00

GS: NoGS

RC: Both

NANO: No

ROLE: Base Metal

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Alternate door and frame. This substance is considered essentially inert for the purposes of Pharos toxics scoring (Pharos CML). Total recycled content confirmed by suppliers for stainless steel is approximately 92% (22% pre-consumer and 70% post-consumer). Documentation from supplier provides the following composition for alloying elements that may individually exceed the declared threshold: max 27% Chromium [7440-47-3; LT- P1]; max 22% Nickel [7440-02-0; LT-1]; max 10% Manganese [7439-96-5; LT- P1]; max 4.4% Copper [7440-50-8; LT-UNK]; max 4.0% Molybdenum [7439-98-7; LT-UNK]; max 2.0% Aluminum [7429-90-5; LT-P1]; max 2.0% Silicon [7440-21-3; LT-UNK]; max 1.1% Tantalum [7440-25-7; LT-UNK]; max 1.0% Cobalt [7440-48-4; LT-1]; max 0.8% Columbium [7440-03-1; LT-UNK]; 0.7% Titanium [7440- 32-6; LT-UNK]. Supplier statement confirms this product is free of mercury.

ZINC

ID: 7440-66-6

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-07-15**

#: **0.02 - 2.00** GS: **LT-P1** RC: **None** NANO: **No** ROLE: **Metallic Coating**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
ACUTE AQUATIC	EU - GHS (H-Statements)	H400 - Very toxic to aquatic life
CHRON AQUATIC	EU - GHS (H-Statements)	H410 - Very toxic to aquatic life with long lasting effects
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Statements)	H250 - Catches fire spontaneously if exposed to air
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Statements)	H260 - In contact with water releases flammable gases which may ignite spontaneously
ENDOCRINE	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters

SUBSTANCE NOTES: Used in galvanized and zinc-plated steel components, including alternate door and frame, spring, bracket, and various mixed hardware.

ALUMINA TRIHYDRATE

ID: 21645-51-2

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-07-15**

#: **0.00 - 0.30** GS: **BM-2** RC: **None** NANO: **No** ROLE: **Filler, Extender**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
RESPIRATORY	AOEC - Asthmagens	Asthmagens (Rs) - sensitizer-induced

SUBSTANCE NOTES: White powder coating available on standard steel door and frame. GreenScreen Benchmark® assessment score of BM-2 was provided by the HPD Builder Tool.

TITANIUM DIOXIDE

ID: 13463-67-7

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-07-15**

#: **0.00 - 0.30** GS: **LT-1** RC: **None** NANO: **No** ROLE: **Pigment**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	US CDC - Occupational Carcinogens	Occupational Carcinogen
CANCER	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CANCER	IARC	Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources
ENDOCRINE	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
CANCER	MAK	Carcinogen Group 3A - Evidence of carcinogenic effects but not sufficient to establish MAK/BAT value
CANCER	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels

SUBSTANCE NOTES: White powder coating available on standard steel door and frame.

UNDISCLOSED

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-07-15**

#: **0.00 - 0.40**

GS: **NoGS**

RC: **None**

NANO: **No**

ROLE: **Pigment Binder**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: White powder coating available on standard steel door and frame. Supplier has shared substance identity under the terms of a non-disclosure agreement; substance to remain proprietary to supplier. Substance has been screened against HPD Priority Lists using the HPD Builder with results disclosed.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

Inherently non-emitting source per LEED®

CERTIFYING PARTY: **Self-declared**

ISSUE DATE: **2019-**

EXPIRY DATE:

CERTIFIER OR LAB: **N/A**

APPLICABLE FACILITIES: **All**

04-10

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: **This product qualifies as an inherently non-emitting source per LEED, as ~99% of the product consists of powder-coated metal and/or plated or anodized metal. As per LEED, "Products that are inherently nonemitting sources of VOCs (stone, ceramic, powder-coated metals, plated or anodized metal, glass, concrete, clay brick, and unfinished or untreated solid wood) are considered fully compliant without any VOC emissions testing if they do not include integral organic-based surface coatings, binders, or sealants."**

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

KEY OPERATED CAM LATCH

HPD URL: **No HPD available**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Optional Latch available. Please contact manufacturer for more information.

MORTISE LOCK PREP

HPD URL: **No HPD available**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Optional Mortise Lock (1-1/8 inch) Prep available. Please contact manufacturer for more information.

Section 5: General Notes



MANUFACTURER INFORMATION

MANUFACTURER: **Babcock-Davis**
ADDRESS: **9300 73rd Avenue North**
Brooklyn Park MN 55428, USA
WEBSITE: **www.babcockdavis.com**

CONTACT NAME: **Sandy McWilliams**
TITLE: **Director, Specification**
PHONE: **888.412.3726**
EMAIL: **SMcWilliams@babcockdavis.com**

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity	GLO Global warming	PHY Physical Hazard (reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive toxicity
DEV Developmental toxicity	MUL Multiple hazards	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	OZO Ozone depletion	LAN Land Toxicity
GEN Gene mutation	PBT Persistent Bioaccumulative Toxic	NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible Benchmark 1
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator Likely Benchmark 1
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS Unknown (no data on List Translator Lists)
BM-U Benchmark Unspecified (insufficient data to benchmark)	

Recycled Types

PreC Preconsumer (Post-Industrial)
PostC Postconsumer
Both Both Preconsumer and Postconsumer
Unk Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.