Levelrock® Brand 3500 Series Floor Underlayments by USG

Health Product Declaration v2.1.1

created via: HPDC Online Builder

CLASSIFICATION: 09 60 00

PRODUCT DESCRIPTION: Levelrock® Brand 3500 Series Floor Underlayments have compressive strengths from 3500 to 4500 psi. For a premium fiber-reinforced underlayment, try Levelrock 3500 FR and 3500 Green FR Floor Underlayment.



Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format C Nested Materials Method

Basic Method

Threshold Disclosed Per

Material

Product

Threshold level

C 100 ppm

1,000 ppm

Per GHS SDS

C Per OSHA MSDS

C Other

Residuals/Impurities

Considered

C Partially Considered

Not Considered

Explanation(s) provided for Residuals/Impurities?

Yes O No

All Substances Above the Threshold Indicated Are:

O Yes Ex/SC O Yes O No Characterized

% weight and role provided for all substances.

○ Yes Ex/SC ○ Yes ○ No Screened

All substances screened using Priority Hazard Lists with results disclosed.

Identified C Yes Ex/SC C Yes © No

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

LEVELROCK® BRAND 3500 SERIES FLOOR UNDERLAYMENTS [CALCIUM SULFATE - HEMIHYDRATE LT-UNK PORTLAND CEMENT LT-P1 | END | CAN UNDISCLOSED LT-UNK UNDISCLOSED LT-UNK LIMESTONE, CALCIUM CARBONATE LT-UNK QUARTZ LT-1 | CAN]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Residuals/Impurities in raw materials that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS are displayed in the HPD when greater than or equal to 1000 ppm. USG uses an outside lab to quantify potential impurities of raw materials. Analytical methods may include but are not limited to; x-ray diffraction, x-ray fluorescence, atomic absorption, ion chromatography, liquid chromatography, and crystalline silica analysis.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

C Yes No

PREPARER: Self-Prepared

VERIFIER: **VERIFICATION #:**

SCREENING DATE: 2019-02-11 PUBLISHED DATE: 2019-02-25

EXPIRY DATE: 2022-02-11



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-standard

LEVELROCK® BRAND 3500 SERIES FLOOR UNDERLAYMENTS

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals/Impurities in raw materials that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS are displayed in the HPD when greater than or equal to 1000 ppm. Naturally occurring raw materials in this product may contain trace amounts of respirable crystalline silica. The accumulative percentage of respirable crystalline silica is expected to exceed the threshold of 1000 ppm. See the SDS on usg.com for occupational exposure information.

OTHER PRODUCT NOTES: This product is manufactured at Southard, OK and Fort Dodge, IA, Gypsum, OH, Torrance, CA, and Baltimore, MD.

CALCIUM SULFATE - HEMIHYDRATE

ID: 10034-76-1

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-02-11		
%: 92.0000 - 97.0000	GS: LT-UNK	RC: PreC	nano: No	ROLE: Setting additive
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
	No hazards found			

SUBSTANCE NOTES: May also use the CAS RN of calcium sulfate hemihydrate CAS RN: 26499-65-0. Crystalline silica is an impurity found in calcium sulfate hemihydrate. See the impurity crystalline silica entry for more information.

PORTLAND CEMENT ID: 65997-15-1 HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2019-02-11

%: 3.0000 - 7.0000 GS: **LT-P1** ROLE: General-purpose cement RC: None NANO: NO HAZARD TYPE AGENCY AND LIST TITLES WARNINGS **ENDOCRINE TEDX - Potential Endocrine Disruptors** Potential Endocrine Disruptor CANCER MAK Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

UNDISCLOSED

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREEN	HAZARD SCREENING DATE: 2019-02-11		
%: 0.1000 - 0.7000	GS: LT-UNK	RC: None	nano: No	ROLE: Dispersant	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
	No hazards found				

SUBSTANCE NOTES: Proprietary ingredient. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. Not on the Living Building Challenge™ (LBC) Red List Chemical Guide (Version 3.1).

UNDISCLOSED

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREEN	HAZARD SCREENING DATE: 2019-02-11		
%: 0.1000 - 0.5000	GS: LT-UNK	RC: None	NANO: No	ROLE: Plasticizer	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
	No hazards found				

SUBSTANCE NOTES: Proprietary ingredient. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. Not on the Living Building Challenge™ (LBC) Red List Chemical Guide (Version 3.1).

LIMESTONE, CALCIUM CARBONATE

ID: 1317-65-3

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENIN	HAZARD SCREENING DATE: 2019-02-11		
%: 0.0500 - 0.1000	GS: LT-UNK	RC: None	nano: No	ROLE: Filler	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
	No hazards found				

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

QUARTZ ID: 14808-60-7

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREE	HAZARD SCREENING DATE: 2019-02-11		
%: Impurity/Residual	GS: LT-1	RC: None	NANO: No	ROLE: Impurity/Residual	

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	IARC	Group 1 - Agent is Carcinogenic to humans
CANCER	US CDC - Occupational Carcinogens	Occupational Carcinogen
CANCER	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CANCER	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CANCER	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CANCER	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CANCER	New Zealand - GHS	6.7A - Known or presumed human carcinogens
CANCER	Japan - GHS	Carcinogenicity - Category 1A
CANCER	Australia - GHS	H350i - May cause cancer by inhalation

 $\hbox{\scriptsize {\tt SUBSTANCE\ NOTES:}}\ \textbf{Impurity\ found\ in\ naturally\ occurring\ raw\ materials.}$



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

UL/GreenGuard Gold Certified

CERTIFYING PARTY: Third Party

ISSUE DATE: 2017- EXPIRY DATE:

CERTIFIER OR LAB: UL

APPLICABLE FACILITIES: All

12-18

Environment

CERTIFICATE URL: https://spot.ul.com/main-

app/products/detail/5ad1f1be55b0e82d946ad696? keywords=levelrock&page_type=Products%20Catalog

CERTIFICATION AND COMPLIANCE NOTES: VOC emissions testing according to the CDPH 01350 v1.1 2010 criteria.



Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.



Section 5: General Notes

Ingredient specific notes are included in Section 2.

MANUFACTURER INFORMATION

MANUFACTURER: USG

ADDRESS: 550 West Adams St.

Chicago IL 60661, US

WEBSITE: usg.com

CONTACT NAME: USG Sustainability

TITLE: Sustainability Manager

PHONE: 1-800-USG4YOU

EMAIL: sustainability@usg.com

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity **END** Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

MAM Mammalian/systemic/organ toxicity

MUL Multiple hazards

NEU Neurotoxicity

OZO Ozone depletion **PBT** Persistent Bioaccumulative Toxic

PHY Physical Hazard (reactive)
REP Reproductive toxicity

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

LAN Land Toxicity

NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insuficient data to benchmark)

Recycled Types

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

Both Both Preconsumer and Postconsumer

Unk Inclusion of recycled content is unknown

None Does not include recycled content

LT-P1 List Translator Possible Benchmark 1 LT-1 List Translator Likely Benchmark 1

LT-1 List Halislator Likely Delicilliant I

LT-UNK List Translator Benchmark Unknown (insufficient

information from List Translator lists to benchmark)

NoGS Unknown (no data on List Translator Lists)

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances
 created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.