

CLASSIFICATION: 09 29 00

PRODUCT DESCRIPTION: USG Sheetrock® Brand Firecode® X Gypsum Panels are composed of fire-resistant gypsum core encased in 100-percent recycled natural-finish face paper and 100-percent recycled liner paper on the back. These panels score and snap easily for quick installation of interior wall and ceiling applications, allowing painting, decorating and the installation of metal or wood almost immediately.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
- Basic Method

Threshold Disclosed Per

- Material
- Product

Threshold level

- 100 ppm
- 1,000 ppm
- Per GHS SDS
- Per OSHA MSDS
- Other

Residuals/Impurities

- Considered
- Partially Considered
- Not Considered

Explanation(s) provided for Residuals/Impurities?
 Yes No

All Substances Above the Threshold Indicated Are:

Characterized Yes Ex/SC Yes No
% weight and role provided for all substances.

Screened Yes Ex/SC Yes No
All substances screened using Priority Hazard Lists with results disclosed.

Identified Yes Ex/SC Yes No
One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE

SHEETROCK® BRAND FIRECODE® X PANELS [GYPSUM LT-UNK CELLULOSE, MICROCRYSTALLINE LT-UNK | RES STARCH LT-UNK SOLID GLASS AND GLASS / MINERAL FIBER (SEE VARIANTS) LT-UNK | CAN POLYVINYL ACETATE (PVA) LT-UNK UNDISCLOSED LT-UNK NAPHTHALENESULFONIC ACID, FORMALDEHYDE POLYMER, CALCIUM SALT LT-P1]

Number of Greenscreen BM-4/BM3 contents ... 0
 Contents highest concern GreenScreen Benchmark or List translator Score ... LT-P1
 Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Residuals/Impurities in raw materials that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS are displayed in the HPD when greater than or equal to 1000 ppm. USG uses an outside lab to quantify potential impurities of raw materials. Analytical methods may include but are not limited to; x-ray diffraction, x-ray fluorescence, atomic absorption, ion chromatography, liquid chromatography, and crystalline silica analysis.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

- Yes
- No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2019-12-18

PUBLISHED DATE: 2019-12-18

EXPIRY DATE: 2022-12-18



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

SHEETROCK® BRAND FIRECODE® X PANELS

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Raw materials in this product may contain trace amounts of respirable crystalline silica. Testing has shown exposures to respirable crystalline silica are not expected to exceed the OSHA Permissible Exposure Level (PEL) during the normal use of this product. See the SDS on usg.com for occupational exposure information. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

OTHER PRODUCT NOTES: This product is made at Aliquippa, PA, Baltimore, MD, Bridgeport, AL, East Chicago, IN, Galena Park, TX, Hagersville, ON, Jacksonville, FL, Montreal, QC, Norfolk, VA, Plaster City, CA, Rainier, OR, Saint John, NB, Shoals, IN, Sigurd, UT, Sperry, IA, Sweetwater, TX, and Washingtonville, PA. Percent ranges displayed for this HPD are for all manufacturing plants that make this product and may vary.

GYPSUM

ID: 13397-24-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-12-18

| | | | | |
|------------------|------------|----------|----------|------------|
| %: 90.00 - 95.00 | GS: LT-UNK | RC: PreC | NANO: No | ROLE: Core |
|------------------|------------|----------|----------|------------|

| HAZARD TYPE | AGENCY AND LIST TITLES | WARNINGS |
|-------------|------------------------|--|
| None found | | No warnings found on HPD Priority Hazard Lists |

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. This product contains 94.6% PreC recycled content. The use of FGD gypsum and the pre-consumer recycled content of Sheetrock® Brand Firecode® X Panels will vary by the manufacturing plant.

CELLULOSE, MICROCRYSTALLINE

ID: 9004-34-6

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-12-18

| | | | | |
|----------------|------------|-----------|----------|------------------|
| %: 3.00 - 7.00 | GS: LT-UNK | RC: PostC | NANO: No | ROLE: Paper face |
|----------------|------------|-----------|----------|------------------|

| HAZARD TYPE | AGENCY AND LIST TITLES | WARNINGS |
|-------------|------------------------|-------------------------------------|
| RESPIRATORY | AOEC - Asthmagens | Asthmagen (Rs) - sensitizer-induced |

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. This product contains 3.4% PostC recycled content.

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2019-12-18**%: **0.10 - 0.50**GS: **LT-UNK**RC: **None**NANO: **No**ROLE: **Binder**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

SOLID GLASS AND GLASS / MINERAL FIBER (SEE VARIANTS)

ID: 65997-17-3

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2019-12-18**%: **0.10 - 0.50**GS: **LT-UNK**RC: **None**NANO: **No**ROLE: **Reinforcing**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

CANCER

EU - GHS (H-Statements)

H351 - Suspected of causing cancer

SUBSTANCE NOTES: As manufactured, continuous filament glass fibers in this product are not respirable. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

POLYVINYL ACETATE (PVA)

ID: 9003-20-7

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2019-12-18**%: **0.01 - 0.05**GS: **LT-UNK**RC: **None**NANO: **No**ROLE: **Adhesive**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

UNDISCLOSEDHAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**HAZARD SCREENING DATE: **2019-12-18**%: **0.01 - 0.20**GS: **LT-UNK**RC: **None**NANO: **No**ROLE: **Core strengthening**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Proprietary ingredient. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. Not on the Living Future - Living Building Red List - Red List substances to avoid in Living Building Challenge v3 projects.

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2019-12-18**

%: **0.01 - 0.07**

GS: **LT-P1**

RC: **None**

NANO: **No**

ROLE: **Dispersant**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: **USG has made an effort to decrease and will ultimately replace this dispersant. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.**

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

UL/GreenGuard Gold Certified

CERTIFYING PARTY: **Third Party**

ISSUE DATE: **2016-**

EXPIRY DATE:

CERTIFIER OR LAB: **UL**

APPLICABLE FACILITIES: **All**

01-29

Environment

CERTIFICATE URL: <https://spot.ul.com/>

CERTIFICATION AND COMPLIANCE NOTES: **Building products and interior finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office and Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m³) fall in the range of 0.5 mg/m³ or less, as specified in CDPH Standard Method v1.2.**

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

USG SHEETROCK® OR BEADEX® BRAND FINISHING PRODUCTS

HPD URL:

<https://www.usg.com/content/usgcom/en/search.html?resourceCenter=true&filters=doc-types%3Ahealth-product-declaration,USG%3Alanguage/english>

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

For high-quality finishing results, USG recommends USG Sheetrock® or Beadex® Brand finishing products. Painting products and systems should be used that comply with recommendations and requirements in Appendices of ASTM C840. For priming and decorating with paint, texture or wall covering, follow manufacturer's directions for materials used. Gypsum Association's Recommended Specification for Levels of Gypsum Board Finish (GA-214) should be referred to in order to determine the level of finishing needed to ensure a surface properly prepared to accept the final decoration. For additional installation information, refer to product submittal sheet.

Section 5: General Notes

The International Agency for Research on Cancer (IARC) in June, 1987, categorized continuous filament glass fibers as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify continuous filament glass fiber as a possible, probable, or confirmed cancer causing material.

MANUFACTURER INFORMATION

MANUFACTURER: **USG**
ADDRESS: **550 West Adams St**
Chicago IL 60661, United States
WEBSITE: **usg.com**

CONTACT NAME: **Stacy Simpson**
TITLE: **Sustainability Manager**
PHONE: **1-800-USG4YOU**
EMAIL: **sustainability@usg.com**

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

| | | |
|---------------------------------------|--|--|
| AQU Aquatic toxicity | GLO Global warming | PHY Physical Hazard (reactive) |
| CAN Cancer | MAM Mammalian/systemic/organ toxicity | REP Reproductive toxicity |
| DEV Developmental toxicity | MUL Multiple hazards | RES Respiratory sensitization |
| END Endocrine activity | NEU Neurotoxicity | SKI Skin sensitization/irritation/corrosivity |
| EYE Eye irritation/corrosivity | OZO Ozone depletion | LAN Land Toxicity |
| GEN Gene mutation | PBT Persistent Bioaccumulative Toxic | NF Not found on Priority Hazard Lists |

GreenScreen (GS)

| | |
|---|--|
| BM-4 Benchmark 4 (prefer-safer chemical) | LT-P1 List Translator Possible Benchmark 1 |
| BM-3 Benchmark 3 (use but still opportunity for improvement) | LT-1 List Translator Likely Benchmark 1 |
| BM-2 Benchmark 2 (use but search for safer substitutes) | LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark) |
| BM-1 Benchmark 1 (avoid - chemical of high concern) | NoGS Unknown (no data on List Translator Lists) |
| BM-U Benchmark Unspecified (insufficient data to benchmark) | |

Recycled Types

PreC Preconsumer (Post-Industrial)
PostC Postconsumer
Both Both Preconsumer and Postconsumer
Unk Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms**Inventory Methods:**

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.