# **Sheetrock® Brand Gypsum Liner Panels** by USG

# **Health Product** Declaration v2.1.1

created via: HPDC Online Builder

CLASSIFICATION: 09 20 00

PRODUCT DESCRIPTION: This 1" paper-faced liner panel with moisture resistance features double beveled edges for easy installation, and is recommended for use in use in fire-resistant USG Shaft Wall Systems and Area Separation Wall Systems, or any UL design where UL Type SLX panels are listed. For more information, refer to USG product submittal sheet WB2278.



# Section 1: Summary

# **Basic Method / Product Threshold**

#### **CONTENT INVENTORY**

# **Inventory Reporting Format**

- Nested Materials Method
- Basic Method

### **Threshold Disclosed Per**

- Material
- Product

## Threshold level

- C 100 ppm
- 1,000 ppm
- Per GHS SDS
- C Per OSHA MSDS C Other

# Residuals/Impurities

- Considered
- C Partially Considered
- Not Considered

Explanation(s) provided for Residuals/Impurities?

Yes No

## All Substances Above the Threshold Indicated Are:

Characterized

% weight and role provided for all substances.

Screened

○ Yes Ex/SC Yes No

All substances screened using Priority Hazard Lists with results disclosed.

Identified

O Yes Ex/SC O Yes O No

All substances disclosed by Name (Specific or Generic) and Identifier.

### CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

**GREENSCREEN SCORE | HAZARD TYPE** 

SHEETROCK® BRAND GYPSUM LINER PANELS [ CALCIUM SULFATE DIHYDRATE LT-UNK CELLULOSE PULP NoGS KAOLIN CLAY LT-UNK | CAN CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE LT-UNK NAPHTHALENESULFONIC ACID, FORMALDEHYDE POLYMER, CALCIUM SALT LT-P1 POTASSIUM SULFATE LT-UNK CALCIUM CARBONATE BM-3 METAPHOSPHORIC ACID (H3P3O9), TRISODIUM SALT LT-UNK

Number of Greenscreen BM-4/BM3 contents ... 1

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-P1

Nanomaterial ... No

### **INVENTORY AND SCREENING NOTES:**

Residuals/Impurities in raw materials that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS are displayed in the HPD when greater than or equal to 1000 ppm. USG uses an outside lab to quantify potential impurities of raw materials. Analytical methods may include but are not limited to; x-ray diffraction, x-ray fluorescence, atomic absorption, ion chromatography, liquid chromatography, and crystalline silica analysis.

### **VOLATILE ORGANIC COMPOUND (VOC) CONTENT**

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified

**CONSISTENCY WITH OTHER PROGRAMS** 

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

C Yes No

PREPARER: Self-Prepared

VERIFIER: VERIFICATION #: **SCREENING DATE: 2019-06-18** PUBLISHED DATE: 2020-03-25 EXPIRY DATE: 2022-06-18

Sheetrock Brand Gypsum Liner Panels hpdrepository.hpd-collaborative.org



# Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

#### SHEETROCK® BRAND GYPSUM LINER PANELS

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Raw materials in this product may contain trace amounts of respirable crystalline silica. Testing has shown exposures to respirable crystalline silica are not expected to exceed the OSHA Permissible Exposure Level (PEL) during the normal use of this product. See the SDS on usg.com for occupational exposure information. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

OTHER PRODUCT NOTES: This product is made at Shoals, IN, Baltimore, MD, and Sweetwater, TX. Percent ranges displayed for this HPD are for all manufacturing plants that make this product and may vary.

#### **CALCIUM SULFATE DIHYDRATE** ID: 10101-41-4

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-06-18		
%: 95.00 - 98.00	GS: LT-UNK	RC: PostC	NANO: <b>No</b>	ROLE: Core
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		D Priority Hazard Lists

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

**CELLULOSE PULP** ID: 65996-61-4

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREE	HAZARD SCREENING DATE: 2019-06-18		
%: <b>1.00 - 2.30</b>	gs: <b>NoGS</b>	RC: Both	nano: <b>No</b>	ROLE: Paper face	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found No warnings found on HPD Priority Hazard Lists					

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

**KAOLIN CLAY** ID: 1332-58-7

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2019-06-18

%: 0.80 - 1.50	GS: LT-UNK	RC: None	nano: <b>No</b>	ROLE: Adhesive
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
CANCER	MAK	Carcinogen Group 3B - Evidence of carcinogen but not sufficient for classification		•

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

### **CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE**

ID: 65997-17-3

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-06-18		
%: 0.25 - 0.30	GS: LT-UNK	RC: None	NANO: <b>No</b>	ROLE: Adhesive
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found No warnings found on HPD Priority Hazard Lis			on HPD Priority Hazard Lists	

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

## NAPHTHALENESULFONIC ACID, FORMALDEHYDE POLYMER, CALCIUM SALT

ID: 37293-74-6

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENII	HAZARD SCREENING DATE: 2019-06-18		
%: <b>0.17 - 0.41</b>	GS: LT-P1	RC: None	NANO: <b>No</b>	ROLE: Dispersant	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found		No warn	ings found or	HPD Priority Hazard Lists	

SUBSTANCE NOTES: USG has made an effort to decrease and will ultimately replace this dispersant. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

POTASSIUM SULFATE ID: 7778-80-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREE	HAZARD SCREENING DATE: 2019-06-18		
%: <b>0.15 - 0.34</b>	GS: LT-UNK	RC: None	nano: <b>No</b>	ROLE: Disspersant	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found No warnings found on HPD Priority Hazard Li				nd on HPD Priority Hazard Lists	

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

CALCIUM CARBONATE ID: 471-34-1

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCRE	HAZARD SCREENING DATE: 2019-06-18		
%: 0.10 - 0.25	GS: <b>BM-3</b>	RC: None	nano: <b>No</b>	ROLE: Adhesive	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found No warnings found on HPD Priority Hazard Lis			on HPD Priority Hazard Lists		

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

## METAPHOSPHORIC ACID (H3P3O9), TRISODIUM SALT

ID: **7785-84-4** 

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-06-18		
%: 0.05 - 0.15	GS: LT-UNK	RC: None	NANO: <b>No</b>	ROLE: Dispersant
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found No warnings found on HPD Priority Hazard Lists				on HPD Priority Hazard Lists

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.



# **Section 3: Certifications and Compliance**

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

### **VOC EMISSIONS**

### **UL/GreenGuard Gold Certified**

ISSUE DATE: 2016-CERTIFYING PARTY: Third Party EXPIRY DATE: CERTIFIER OR LAB: UL 01-29 APPLICABLE FACILITIES: All Environment

CERTIFICATE URL: https://spot.ul.com/

CERTIFICATION AND COMPLIANCE NOTES: Building products and interior finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office and Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m³) fall in the range of 0.5 mg/m³ or less, as specified in CDPH Standard Method v1.2.



# **Section 4: Accessories**

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.



# Section 5: General Notes

The International Agency for Research on Cancer (IARC) in June, 1987, categorized continuous filament glass fibers as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify continuous filament glass fiber as a possible, probable, or confirmed cancer causing material.

#### MANUFACTURER INFORMATION

MANUFACTURER: USG

ADDRESS: 550 W. Adams Street Chicago IL 60661, United States

WEBSITE: usg.com

CONTACT NAME: Stacy Simpson

TITLE: Sustainability Manager

PHONE: 1-800-USG4YOU

EMAIL: sustainability@usg.com

#### **KEY**

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

#### **Hazard Types**

**AQU** Aquatic toxicity

**CAN** Cancer

**DEV** Developmental toxicity **END** Endocrine activity

**EYE** Eye irritation/corrosivity

**GEN** Gene mutation

**GLO** Global warming

MAM Mammalian/systemic/organ toxicity

**MUL** Multiple hazards

**NEU** Neurotoxicity

**OZO** Ozone depletion

**PBT** Persistent Bioaccumulative Toxic

PHY Physical Hazard (reactive)
REP Reproductive toxicity

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

**LAN** Land Toxicity

NF Not found on Priority Hazard Lists

#### GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insuficient data to benchmark)

## **Recycled Types**

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

**Both** Both Preconsumer and Postconsumer

Unk Inclusion of recycled content is unknown

None Does not include recycled content

LT-P1 List Translator Possible Benchmark 1 LT-1 List Translator Likely Benchmark 1

LT-UNK List Translator Benchmark Unknown (insufficient

information from List Translator lists to benchmark)

NoGS Unknown (no data on List Translator Lists)

### **Other Terms**

## **Inventory Methods:**

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances
  created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.