Sheetrock® Brand UltraLight Panels Firecode® X by USG

Health Product Declaration v2.1.1

created via: HPDC Online Builder

CLASSIFICATION: 09 20 00

PRODUCT DESCRIPTION: The first and lightest 5/8" Type X panel available that's listed by UL for use in fire-rated partitions when installed either vertically or horizontally with aligned tapered edges on standard and equivalent ULapproved 25-gauge studs (per UL Design U419), USG Sheetrock® Brand UltraLight Panels Firecode® X are ideal for commercial or residential applications where 5/8" Type X panels are required. This panel can also be used in any UL design where UL Type ULX or ULIX panels are listed. For more information, refer to USG product submittal sheet WB2598.



Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format C Nested Materials Method Basic Method

Threshold Disclosed Per

Material Product

Threshold level

- C 100 ppm
- ① 1,000 ppm
- Per GHS SDS Per OSHA MSDS
- Other

Residuals/Impurities

- Considered
- C Partially Considered
- Not Considered

Explanation(s) provided for Residuals/Impurities? Yes No

All Substances Above the Threshold Indicated Are:

% weight and role provided for all substances.

 ○ Yes Ex/SC Yes No Characterized

O Yes Ex/SC O Yes O No Screened

All substances screened using Priority Hazard Lists with results disclosed.

Identified O Yes Ex/SC O Yes O No

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SHEETROCK® BRAND ULTRALIGHT PANELS FIRECODE® X [GYPSUM LT-UNK VERMICULITE NOGS CELLULOSE, MICROCRYSTALLINE NOGS CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE LT-UNK UNDISCLOSED LT-UNK STARCH LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-UNK

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Residuals/Impurities in raw materials that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS are displayed in the HPD when greater than or equal to 1000 ppm. USG uses an outside lab to quantify potential impurities of raw materials. Analytical methods may include but are not limited to; x-ray diffraction, x-ray fluorescence, atomic absorption, ion chromatography, liquid chromatography, and crystalline silica analysis.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

C Yes No

PREPARER: Self-Prepared

VERIFIER: VERIFICATION #: SCREENING DATE: 2019-06-11 PUBLISHED DATE: 2019-12-10

EXPIRY DATE: 2022-06-11



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

SHEETROCK® BRAND ULTRALIGHT PANELS FIRECODE® X

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Raw materials in this product may contain trace amounts of respirable crystalline silica. Testing has shown exposures to respirable crystalline silica are not expected to exceed the OSHA Permissible Exposure Level (PEL) during the normal use of this product. See the SDS on usg.com for occupational exposure information. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

OTHER PRODUCT NOTES: This product is made at Aliquippa, PA, Bridgeport, AL, Jacksonville, FL, Rainer, OR, Plaster City, CA, Sperry, IA, Sweetwater, TX, and Washingtonville, PA. Percent ranges displayed for this HPD are for all manufacturing plants that make this product and may vary.

GYPSUM				ID: 13397-24-5	
HAZARD SCREENING METHOD:	Pharos Chemical and Materials Library	HAZARD SCREENING DATE: 2019-06-11			
%: 85.50 - 93.00	GS: LT-UNK	RC: PreC	nano: No	ROLE: Core	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found		No warnings found on HPD Priority Hazard Lists			

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. The use of FGD gypsum and the pre-consumer recycled content of Sheetrock® Brand UltraLight Panels Firecode® X will vary by the manufacturing plant.

VERMICULITE ID: 1318-00-9 HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2019-06-11

GS: NoGS %: 5.00 - 7.00 RC: None NANO: **NO**

HAZARD TYPE AGENCY AND LIST TITLES WARNINGS

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

CELLULOSE, MICROCRYSTALLINE

ID: 9004-34-6

BOLE: Fire endurance

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREEN	HAZARD SCREENING DATE: 2019-06-11		
%: 5.00 - 7.00	gs: NoGS	RC: PostC	NANO: No	ROLE: Paper face	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found No warnings found on HPD Priority Hazard I				d on HPD Priority Hazard Lists	

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE

ID: 65997-17-3

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-06-11			
%: 1.40 - 4.00	GS: LT-UNK	RC: None	nano: No	ROLE: Reinforcement	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found			No warnings fo	und on HPD Priority Hazard Lists	

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

UNDISCLOSED

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREE	HAZARD SCREENING DATE: 2019-06-11			
%: 0.70 - 0.90	GS: LT-UNK	RC: None	nano: No	ROLE: Core strengthening		
HAZARD TYPE	AGENCY AND LIST TITLES	WARNING	GS			
None found			No warnin	gs found on HPD Priority Hazard Lists		

SUBSTANCE NOTES: Proprietary ingredient. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. Not on the Living Building Challenge™ (LBC) Red List Chemical Guide (Version 3.1)

STARCH				ID: 9005-25-8
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-06-11		
%: 0.10 - 0.20	gs: LT-UNK	RC: None	nano: No	ROLE: Binder
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No v	varnings found on h	HPD Priority Hazard Lists

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 100 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

UL/GreenGuard Gold Certified

ISSUE DATE: 2016-CERTIFYING PARTY: Third Party EXPIRY DATE: 2020-CERTIFIER OR LAB: UL 01-29 01-29 APPLICABLE FACILITIES: All Environment

CERTIFICATE URL: https://spot.ul.com

CERTIFICATION AND COMPLIANCE NOTES: VOC emissions testing according to the CDPH 01350 v1.1 2010 criteria.



Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

USG SHEETROCK® OR BEADEX® BRAND FINISHING PRODUCTS

HPD URL:

https://www.usg.com/content/usgcom/en/search.html? resourceCenter=true&filters=doc-types%3Ahealthproduct-declaration, USG %3Alanguage/english

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

For high-quality finishing results, USG recommends USG Sheetrock® or Beadex® Brand finishing products. Painting products and systems should be used that comply with recommendations and requirements in Appendices of ASTM C840. For priming and decorating with paint, texture or wall covering, follow manufacturer's directions for materials used. Gypsum Association's Recommended Specification for Levels of Gypsum Board Finish (GA-214) should be referred to in order to determine the level of finishing needed to ensure a surface properly prepared to accept the final decoration. For additional installation information, refer to product submittal sheet.



Section 5: General Notes

The International Agency for Research on Cancer (IARC) in June, 1987, categorized continuous filament glass fibers as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify continuous filament glass fiber as a possible, probable, or confirmed cancer causing material.

MANUFACTURER INFORMATION

MANUFACTURER: USG

ADDRESS: 550 W. Adams Street Chicago IL 60661, United States

WEBSITE: usg.com

CONTACT NAME: USG Sustainability

TITLE: Sustainability Manager

PHONE: 1-800-USG4YOU

EMAIL: sustainability@usg.com

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity **END** Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

MAM Mammalian/systemic/organ toxicity

MUL Multiple hazards

NEU Neurotoxicity

OZO Ozone depletion

PBT Persistent Bioaccumulative Toxic

PHY Physical Hazard (reactive)
REP Reproductive toxicity

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

LAN Land Toxicity

NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insuficient data to benchmark)

Recycled Types

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

Both Both Preconsumer and Postconsumer

Unk Inclusion of recycled content is unknown

None Does not include recycled content

LT-P1 List Translator Possible Benchmark 1 LT-1 List Translator Likely Benchmark 1

LT-UNK List Translator Benchmark Unknown (insufficient

information from List Translator lists to benchmark)

NoGS Unknown (no data on List Translator Lists)

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances
 created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.