

USG Sheetrock® Brand Glass-Mat Liner Panels Mold Tough® by USG

Health Product Declaration v2.1.1

created via: HPDC Online Builder

CLASSIFICATION: 09 20 00

PRODUCT DESCRIPTION: This 1" panel features double-beveled edges for easy installation, as well as a noncombustible, moisture- and mold-resistant gypsum core that's encased in a moisture- and mold-resistant glass mat. The panel is guaranteed for up to 12-months of limited moisture exposure, making it ideal as a direct substitute for USG Sheetrock® Brand Gypsum Liner Panels and USG Sheetrock® Brand Mold Tough® Gypsum Liner Panels in all USG Shaft Wall and Area Separation Wall Systems, or in any UL design where UL Type SLX panels are listed. For more information, refer to USG product submittal sheet WB2483.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- ☐ Nested Materials Method
☒ Basic Method

Threshold Disclosed Per

- ☐ Material
☒ Product

Threshold level

- ☐ 100 ppm
☒ 1,000 ppm
☐ Per GHS SDS
☐ Per OSHA MSDS
☐ Other

Residuals/Impurities

- ☒ Considered
☐ Partially Considered
☐ Not Considered

Explanation(s) provided for Residuals/Impurities?

- ☒ Yes ☐ No

All Substances Above the Threshold Indicated Are:

Characterized ☐ Yes Ex/SC ☒ Yes ☐ No
% weight and role provided for all substances.

Screened ☐ Yes Ex/SC ☒ Yes ☐ No
All substances screened using Priority Hazard Lists with results disclosed.

Identified ☐ Yes Ex/SC ☒ Yes ☐ No
All substances disclosed by Name (Specific or Generic) and Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE

USG SHEETROCK® BRAND GLASS-MAT LINER PANELS MOLD TOUGH® [GYPSUM LT-UNK CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE LT-UNK FLY ASH LT-UNK POLY(METHYLHYDROSILOXANE) NoGS NAPHTHALENESULFONIC ACID, FORMALDEHYDE POLYMER, CALCIUM SALT LT-P1 2-PYRIDINETHIOL, 1-OXIDE, SODIUM SALT LT-P1 | MUL]

Number of Greenscreen BM-4/BM3 contents ... 0
Contents highest concern GreenScreen Benchmark or List translator Score ... LT-P1
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Residuals/Impurities in raw materials that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS are displayed in the HPD when greater than or equal to 1000 ppm. USG uses an outside lab to quantify potential impurities of raw materials. Analytical methods may include but are not limited to; x-ray diffraction, x-ray fluorescence, atomic absorption, ion chromatography, liquid chromatography, and crystalline silica analysis.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

- ☐ Yes
☒ No

PREPARER: Self-Prepared

VERIFIER:
VERIFICATION #:

SCREENING DATE: 2019-06-11

PUBLISHED DATE: 2019-10-02

EXPIRY DATE: 2022-06-11



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

USG SHEETROCK® BRAND GLASS-MAT LINER PANELS MOLD TOUGH®

PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES CONSIDERED: Yes
RESIDUALS AND IMPURITIES NOTES: Raw materials in this product may contain trace amounts of respirable crystalline silica. Testing has shown exposures to respirable crystalline silica are not expected to exceed the OSHA Permissible Exposure Level (PEL) during the normal use of this product. See the SDS on usg.com for occupational exposure information. No Residuals or Impurities are expected to be present at or above the 100 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.	
OTHER PRODUCT NOTES: This product is made at Baltimore, MD, Plaster City, CA, Shoals, IN, and Sweetwater, TX. Percent ranges displayed for this HPD are for all manufacturing plants that make this product and may vary.	

GYPSUM		ID: 13397-24-5
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-06-11
%: 93.00 - 97.00	GS: LT-UNK	RC: PreC NANO: No ROLE: Core
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists
SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. The use of FGD gypsum and the pre-consumer recycled content of USG Sheetrock® Brand Glass-Mat Liner Panels Mold Tough® will vary by the manufacturing plant.		

CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE		ID: 65997-17-3
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-06-11
%: 3.00 - 6.00	GS: LT-UNK	RC: None NANO: No ROLE: Reinforcement
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists
SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.		

FLY ASH	ID: 68131-74-8
---------	----------------

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-06-11		
%: 0.30 - 0.50	GS: LT-UNK	RC: PreC	NANO: No	ROLE: Catalyst
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.				

POLY(METHYLHYDROSILOXANE)			ID: 63148-57-2		
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2019-06-11		
#: 0.20 - 0.40		GS: NoGS	RC: None	NANO: No	ROLE: Water repellant
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS		
None found			No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.					

NAPHTHALENESULFONIC ACID, FORMALDEHYDE POLYMER, CALCIUM SALT				ID: 37293-74-6
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-06-11		
%: 0.01 - 0.40	GS: LT-P1	RC: None	NANO: No	ROLE: Dispersant
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: USG has made an effort to decrease and will ultimately replace this dispersant. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.				

2-PYRIDINETHIOL, 1-OXIDE, SODIUM SALT			ID: 3811-73-2		
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2019-06-11		
%: 0.01 - 0.10	GS: LT-P1	RC: None	NANO: No	ROLE: Biocide	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters			
SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.					

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

UL/GreenGuard Gold Certified

CERTIFYING PARTY: Third Party	ISSUE DATE: 2016-	EXPIRY DATE: 2020-	CERTIFIER OR LAB: UL
APPLICABLE FACILITIES: All	01-29	01-29	Environment
CERTIFICATE URL: https://spot.ul.com			

CERTIFICATION AND COMPLIANCE NOTES: **VOC emissions testing according to the CDPH 01350 v1.1 2010 criteria.**

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

The International Agency for Research on Cancer (IARC) in June, 1987, categorized continuous filament glass fibers as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify continuous filament glass fiber as a possible, probable, or confirmed cancer causing material.



MANUFACTURER INFORMATION

MANUFACTURER: **USG**

ADDRESS: **550 W. Adams Street
Chicago IL 60661, United States**

WEBSITE: **usg.com**

CONTACT NAME: **Stacy Simpson**

TITLE: **Sustainability Manager**

PHONE: **1-800-USG4YOU**

EMAIL: **sustainability@usg.com**

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

MAM Mammalian/systemic/organ toxicity

MUL Multiple hazards

NEU Neurotoxicity

OZO Ozone depletion

PBT Persistent Bioaccumulative Toxic

PHY Physical Hazard (reactive)

REP Reproductive toxicity

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

LAN Land Toxicity

NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insufficient data to benchmark)

LT-P1 List Translator Possible Benchmark 1

LT-1 List Translator Likely Benchmark 1

LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)

NoGS Unknown (no data on List Translator Lists)

Recycled Types

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

Both Both Preconsumer and Postconsumer

Unk Inclusion of recycled content is unknown

None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material

Nested Method / Product Threshold Substances listed within each material per threshold indicated per product

Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.